3430H2F200RTDF <

CGS | CGS 3430

TE Internal #: 5-2176562-7 200 ohm, Surface Mount Power Resistor, Thick Film, 1020, 2 W, 1 %, ±100 ppm/°C, Solder, 2 Terminations, .6 mm [.024 in] Height, CGS 3430

View on TE.com >





Resistance Value: 200Ω

Resistor Type: Power Resistor

Element Type: Thick Film

Package Size Code: 1020

Power Rating: 2W

Features

TE connectivity

Product Type Features

Resistor Type	Power Resistor
Element Type	Thick Film
Package Size Code	1020
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Operating Voltage	200 V
Resistance Value	200 Ω
Power Rating	2 W
Resistance Class	Up to 1kΩ
Passive Component Tolerance	1 %
Termination Features	
Surface Mount Resistor Termination Type	Solder
Number of Terminations	2

3430H2F200RTDF

200 ohm, Surface Mount Power Resistor, Thick Film, 1020, 2 W, 1 %, ±100 ppm/°C, Solder, 2 Terminations, .6 mm [.024 in] Height, CGS 3430



Dimensions

Product Height	.6 mm[.024 in]
Product Length	2.45 mm[.096 in]
Product Width	5 mm[.197 in]
Usage Conditions	
Operating Temperature Range	-55 – 155 °C
Temperature Coefficient	±100 ppm/°C
Packaging Features	
Packaging Method	Taped & Reeled
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE

Halogen Content

Solder Process Capability

2024 (241) Does not contain REACH SVHC

BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.

Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

3430H2F200RTDF

200 ohm, Surface Mount Power Resistor, Thick Film, 1020, 2 W, 1 %, ±100 ppm/°C, Solder, 2 Terminations, .6 mm [.024 in] Height, CGS 3430





Also in the Series | CGS 3430



Documents

Product Drawings 3430 H2 1% 200R 100ppm 1k RL English

CAD Files

Customer View Model

ENG_CVM_CVM_5-2176562-7_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-2176562-7_BA.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_5-2176562-7_BA.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Datasheet - CGS 3430 Series

English

Automotive Grade Wide Terminal Chip Resistor - Type 3430 Series

English