

TE Internal #: 5051426-2

SHV Connector, Plug, Bayonet, .3 GHz, Cable-to-Board, 1 Position, Sealable, Wire & Cable, Cable Mount (Free-Hanging), -55 – 155 °C

[-67 – 311 °F]

View on TE.com >



Connectors > RF Connectors > Coax Connectors











RF Interface: SHV

RF Connector Style: Plug

RF Connector Mated Outer Diameter (Approximate): 14.43 mm [.568 in]

Compatible With RF Cable Type: Belden 9209, Belden 9269, Belden 9291, RG 124, RG 140, RG 210, RG 59, RG 59A, RG 59B, RG

62, RG 62A, RG 62B

RF Connector Coupling Mechanism: Bayonet

Features

Product Type Features

Froduct Type realures	
Connector Seal & Plug Type	Gasket
RF Interface	SHV
RF Connector Style	Plug
Compatible With RF Cable Type	Belden 9209, Belden 9269, Belden 9291, RG 124, RG 140, RG 210, RG 59, RG 59A, RG 59B, RG 62, RG 62A, RG 62B
Connector System	Cable-to-Board
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	1
Number of Coaxial Contacts	1
Body Features	

Straight

Cable Connector Orientation



Body Material	Brass
Body Plating Material	Silver
Contact Features	
Crimp Type	Dual Crimp
RF Connector Center Contact Underplating Material	Nickel
RF Connector Center Contact Plating Material	Gold (Au)
RF Connector Center Contact Material	Beryllium Copper
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
RF Connector Coupling Mechanism	Bayonet
Connector Mounting Type	Cable Mount (Free-Hanging)
RF Contact Captivation Method	Mechanical
Detent	With
Dimensions	
RF Connector Mated Outer Diameter (Approximate)	14.43 mm[.568 in]
Usage Conditions	
Operating Temperature Range	-55 – 155 °C[-67 – 311 °F]
Operation/Application	
Operating Frequency	.3 GHz
Packaging Features	
Packaging Method	Carton
Other	
Dielectric Material	PTFE

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)



Candidate List Declared Against: JUNE 2023 (235)

SVHC > Threshold:

Pb (3.7% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in
	other sources.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts
























Customers Also Bought






















Documents

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_5051426-2_A1.2d_dxf.zip

English

Customer View Model

ENG_CVM_5051426-2_A1.3d_igs.zip

English

SHV Connector, Plug, Bayonet, .3 GHz, Cable-to-Board, 1 Position, Sealable, Wire & Cable, Cable Mount (Free-Hanging), -55 – 155 °C [-67 – 311 °F]



Customer View Model ENG_CVM_5051426-2_A1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.