



Terminals & Splices > Quick Disconnects > ULTRA POD: Straight, Receptacle Assembly, Tin Plated, 0.25 inch



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: .32 – .82 mm²

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

[All ULTRA POD: Straight, Receptacle Assembly, Tin Plated, 0.25 inch \(13\)](#)

Features

Product Type Features

|                 |     |
|-----------------|-----|
| Insertion Force | Low |
|-----------------|-----|

Configuration Features

|                                   |               |
|-----------------------------------|---------------|
| Compatible With Wire & Cable Type | Discrete Wire |
| Connection Capacity               | Single        |

Electrical Characteristics

|                |       |
|----------------|-------|
| Voltage Rating | 600 V |
|----------------|-------|

Body Features

|                     |       |
|---------------------|-------|
| Insulation Material | Nylon |
|---------------------|-------|

Contact Features

|                                |                 |
|--------------------------------|-----------------|
| Quick Disconnect Terminal Type | Receptacle      |
| Mating Tab Width               | 6.35 mm[.25 in] |
| Mating Tab Thickness           | .81 mm[.032 in] |
| Terminal Orientation           | Straight        |



|                           |         |
|---------------------------|---------|
| Contact Base Material     | Brass   |
| Terminal Plating Material | Tin     |
| Crimp Type                | F-Crimp |
| Barrel Type               | Open    |

Termination Features

|                       |              |
|-----------------------|--------------|
| Product Terminates To | Wire & Cable |
|-----------------------|--------------|

Mechanical Attachment

|                         |      |
|-------------------------|------|
| Wire Insulation Support | With |
|-------------------------|------|

Dimensions

|                                      |                             |
|--------------------------------------|-----------------------------|
| Product Length                       | 34.67 mm[1.365 in]          |
| Compatible Insulation Diameter Range | 2.29 – 3.3 mm[.09 – .13 in] |
| Terminal Material Thickness          | .41 mm[.016 in]             |
| Wire Size                            | .32 – .82 mm²               |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Insulation Option           | Fully Insulated            |
| Operating Temperature Range | -40 – 150 °C[-40 – 302 °F] |

Industry Standards

|                                             |           |
|---------------------------------------------|-----------|
| Compatible With Agency/Standards Products   | CSA, UL   |
| UL Flammability Rating                      | UL 94V-2  |
| Compatible With Approved Standards Products | UL E66717 |

Packaging Features

|                    |            |
|--------------------|------------|
| Packaging Quantity | 2000       |
| Packaging Method   | Strip/Reel |

Other

|              |         |
|--------------|---------|
| Barrel Color | Natural |
|--------------|---------|

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

|                                               |                                         |
|-----------------------------------------------|-----------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                               |
| EU ELV Directive 2000/53/EC                   | Compliant                               |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006        |                                         |



Current ECHA Candidate List: JAN 2025  
(247)  
Candidate List Declared Against: JAN 2025  
(247)  
Does not contain REACH SVHC

|                           |                                                                                     |
|---------------------------|-------------------------------------------------------------------------------------|
| Halogen Content           | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability                                        |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 314916-1  
INSER TL 250 U-POD STR IS9725



TE Part # 90165-1  
DAHT 250 FASTON REC 18-14 ASSY



TE Part # 2217483-2  
KIT, BTLI, DOUBLE ACTION HEAD



TE Part # 1969161-5  
ULTRA-POD 250 ASY REC 0.3-0.8 MM2 TPBR



TE Part # 1852889-1  
MACH,U-POD.250 SAPR090F130F LM



TE Part # 2217483-1  
KIT, BTLI, DOUBLE ACTION HEAD



TE Part # 91514-1  
CCII FASTON 250 REC 22-18 ASSY



TE Part # 90166-1  
DAHT 250 FASTON REC 22-18 ASSY



TE Part # 1855530-1  
[ULTRA POD/FA SAPR090F140F LM CUT](#)

TE Part # 314917-1  
[EXT TL 250 U-POD STR IS9726](#)

Also in the Series | [Ultra-Pod 250](#)

[Insertion & Extraction Tools\(2\)](#)

[Quick Disconnects\(43\)](#)

Customers Also Bought

TE Part #63306-2  
[250 FASTON REC 18-14 AWG TPBR](#)

TE Part #63561-1  
[SPLICE 10000-16000 CMA 031BR](#)

TE Part #42110-3  
[RING TERMINAL 18-14 AWG BR](#)

TE Part #34143  
[PG R 22-16 COMM 22-18 MIL 4](#)

TE Part #1-324581-1  
[TERMINAL,PG SPD FLG 12-10 6](#)

TE Part #2-520102-2  
[ULTRA-FAST 250 ASSEMBLY TAB 22-18 AWG BR](#)

TE Part #60376-1  
[PIN 090 RECEPTACLE 20-14 AWG TPPHBZ](#)

TE Part #469542-3  
[FLOATING SHEAR](#)

TE Part #41450  
[250 FASTON REC 14-10 AWG TPBR](#)

TE Part #41449  
[250 FASTON REC 14-10 AWG BR](#)



Documents

Product Drawings

ULTRA-POD 250 ASSY REC 22-18 AWG TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_520988-2\_F.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_520988-2\_F.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_520988-2\_F.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Ultra-Fast and Ultra Fast Plus

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English

UL Report

English