TE Internal #: 52937-1

Spring Spade Terminal, 16 – 14 AWG, #10 Stud, 4.82 mm [.19 in]

Stud Diameter, Closed Barrel, Straight, Tin Plating, Partially

Insulated

View on TE.com >



Terminals & Splices > Spade Terminals > PIDG Short Spring Spade Tongue Terminals











Spade Terminal Type: Spring Spade Terminal

Wire Size: 2050 – 5180 CMA

Stud Size: #10

All PIDG Short Spring Spade Tongue Terminals (38)

Features

Product Type Features

rioduct Type reduces	
Stud Size	#10
Sealable	No
Wire Insulation Support Retention Type	Insulation Support
Electrical Characteristics	
Voltage Rating	300 V
Body Features	
Insulation Sleeve Color	Blue
Stripe Color	Blue
Contact Features	
Spade Terminal Type	Spring Spade Terminal

Closed

Straight

Tin

Mechanical Attachment

Terminal Orientation

Terminal Plating Material

Barrel Type



Wire Insulation Support	With
Dimensions	
Wire Size	2050 – 5180 CMA
Stud Diameter	4.82 mm[.19 in]
Tongue Thickness	.79 mm[.031 in]
Product Length	23.06 mm[.908 in]
Compatible Insulation Diameter (Max)	4.32 mm[.17 in]
Compatible Insulation Diameter Range	2.92 – 4.31 mm[.115 – .17 in]
Usage Conditions	
Insulation Option	Partially Insulated
Operation/Application	
Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	4000
Packaging Method	Tape Mounted

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













Customers Also Bought























Documents

Product Drawings

TERMINAL, PIDG SPR SPD 16-14 10

English

CAD Files

Customer View Model

ENG_CVM_CVM_52937-1_T.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_52937-1_T.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_52937-1_T.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Instruction Sheets

AMP* PIDG* (VINYL) & PLASTI-GRIP* SHORT SPRING SPADE TERMINALS FOR BAR

English

Instruction Sheet (U.S.)

English

Instruction Sheet (U.S.)

English

Agency Approvals

Spring Spade Terminal, 16 – 14 AWG, #10 Stud, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Partially Insulated



CSA Certificate

English