


TE Internal #: 52943-1 Spring Spade Terminal, 12 – 10 AWG, #10 Stud, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Partially Insulated

View on TE.com >



Terminals & Splices > Spade Terminals > PIDG Short Spring Spade Tongue Terminals



Spade Terminal Type: Spring Spade Terminal

Wire Size: 5180 – 13100 CMA

Stud Size: **#10**

All PIDG Short Spring Spade Tongue Terminals (38)

Features

Product Type Features

| Stud Size | #10 |
|--|-----------------------|
| Sealable | No |
| Wire Insulation Support Retention Type | Insulation Support |
| Electrical Characteristics | |
| Voltage Rating | 300 V |
| Body Features | |
| Insulation Sleeve Color | Yellow |
| Stripe Color | Yellow |
| Contact Features | |
| Spade Terminal Type | Spring Spade Terminal |
| Barrel Type | Closed |
| Terminal Orientation | Straight |
| Terminal Plating Material | Tin |
| Mechanical Attachment | |
| | |

Spring Spade Terminal, 12 – 10 AWG, #10 Stud, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Partially Insulated



| Wire Insulation Support | With |
|---------------------------------------|------------------------------|
| Dimensions | |
| Wire Size | 5180 – 13100 CMA |
| Stud Diameter | 4.82 mm[.19 in] |
| Tongue Thickness | .99 mm[.039 in] |
| Product Length | 27.94 mm[1.1 in] |
| Compatible Insulation Diameter (Max) | 6.35 mm[.25 in] |
| Compatible Insulation Diameter Range | 3.81 – 6.35 mm[.15 – .25 in] |
| Usage Conditions | |
| Insulation Option | Partially Insulated |
| Operation/Application | |
| Compatible With Wire Base Material | Copper |
| Compatible With Wire Plating Material | Tin |
| Industry Standards | |
| Government Qualified Terminal | No |
| Packaging Features | |
| Packaging Quantity | 2500 |

Packaging Method

Tape Mounted

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability |
| Product Compliance Disclaimer | |

C For support call+1 800 522 6752

Spring Spade Terminal, 12 – 10 AWG, #10 Stud, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Partially Insulated



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






TE Part # 59239-4 HHHT PIDG PG 12-10 ASSY

Customers Also Bought



Spring Spade Terminal, 12 – 10 AWG, #10 Stud, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Partially Insulated







Documents

Product Drawings TERMINAL, PIDG SPR SPD 12-10 10

English

CAD Files Customer View Model ENG_CVM_CVM_52943-1_L.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_52943-1_L.3d_igs.zip

English

Customer View Model

```
ENG_CVM_CVM_52943-1_L.3d_stp.zip
```

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Instruction Sheets AMP* PIDG* (VINYL) & PLASTI-GRIP* SHORT SPRING SPADE TERMINALS FOR BAR English

Instruction Sheet (U.S.)

English

Instruction Sheet (U.S.)

English

Agency Approvals

C For support call+1 800 522 6752

Spring Spade Terminal, 12 – 10 AWG, #10 Stud, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Partially Insulated



UL Report

English