

SOLISTRAND

TE Internal #: 53832-1 Spring Spade Terminal, 22 AWG, #10 Stud, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Uninsulated View on TE.com >



Terminals & Splices > Spade Terminals



Spade Terminal Type: Spring Spade Terminal

Wire Size: 509 – 3260 CMA

Stud Size: **#10**

Features

Product Type Features

Stud Size

Sealable	No
Wire Insulation Support Retention Type	Non-Insulation Support
Contact Features	
Spade Terminal Type	Spring Spade Terminal
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Tin
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	509 – 3260 CMA
Stud Diameter	4.82 mm[.19 in]
Tongue Thickness	.79 mm[.031 in]
Product Length	17.4 mm[.685 in]
Barrel Inside Diameter	3.58 mm[.141 in]

C For support call+1 800 522 6752

53832-1

Spring Spade Terminal, 22 AWG, #10 Stud, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Uninsulated



Usage Conditions

Insulation Option	Uninsulated
Operation/Application	
Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Method	Loose Piece
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE

2024 (241) Does not contain REACH SVHC

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Halogen Content

Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

53832-1

Spring Spade Terminal, 22 AWG, #10 Stud, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Uninsulated





Customers Also Bought



SOLIS R 22-16 COMM 22-18MIL 10

TERMINAL, SOLIS R 16-14 1/2

SOLIS SPDFLG 22-16COM22-18MIL6

DAHT PG PIDG 26-16 ASSY





Documents

53832-1

Spring Spade Terminal, 22 AWG, #10 Stud, 4.82 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Uninsulated



Product Drawings SOLIS SP SPD22-16COM22-18MIL10

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_53832-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_53832-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_53832-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals UL Report

English