AMP

TE Internal #: 53894-4

Housing, Plug / Receptacle, Crimp & Solder, Wire-to-Wire, UL 94V-

2, 1 Position, 1 Row, 600 VAC, Rectangular Wire & Cable

Connectors & Housings

View on TE.com >



Connectors > Rectangular Connectors > Standard Rectangular Connectors











Connector Product Type: Housing

Connector & Housing Type: Plug, Receptacle

Termination Method to Wire & Cable: Crimp & Solder

Connector System: Wire-to-Wire

Contact Retention Within Housing: With

Features

Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Plug, Receptacle
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Signal Positions	0
Number of Power Positions	1
Number of Positions	1
Number of Rows	1
Electrical Characteristics	
Operating Voltage	600 VAC

Body Features



Contact Features	
Contact Type	Blade
Contact Retention Within Housing	With
Contact Current Rating (Max)	31 A
Termination Features	
Termination Method to Wire & Cable	Crimp & Solder
Mechanical Attachment	
Connector Mounting Type	Panel Mount
Housing Features	
Housing Material	Polycarbonate
Dimensions	
Connector Width	8.05 mm[.317 in]
Connector Height	8.05 mm[.317 in]
Wire Size	18 – 12 AWG
Connector Length	24.71 mm[.973 in]
Usage Conditions	
Operating Temperature Range	-40 – 75 °C[-40 – 167 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
Compatible With Agency/Standards Products	CSA, UL
UL Rating	Recognized
Compatible With Approved Standards Products	UL E28476
CSA Rating	Certified, LR 7189
UL Flammability Rating	UL 94V-2
Packaging Features	
Packaging Quantity	200
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts




Customers Also Bought























Documents

Product Drawings

HSG ASSY,PWR LK,SRS1,1 POS,RED

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_53894-4_L.3d_igs.zip

English

Customer View Model

ENG_CVM_53894-4_L.3d_stp.zip

English

Customer View Model

ENG_CVM_53894-4_L.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Application Specification

Japanese

Power-Lock 75 Series Contacts

Japanese

Instruction Sheets

Housing, Plug / Receptacle, Crimp & Solder, Wire-to-Wire, UL 94V-2, 1 Position, 1 Row, 600 VAC, Rectangular Wire & Cable Connectors & Housings



Instruction Sheet (U.S.)

English

Agency Approvals

Agency Approval Document

English