OEG Miniature Relay PCF

TE Internal #: 5414394-1

TE Internal Description: JACK, VERT, 75OHM, PCB, BNC

View on TE.com >



Connectors > RF Connectors > Coax Connectors











RF Interface: BNC

RF Connector Style: Jack

RF Connector Mated Outer Diameter (Approximate): 14.53 mm [.572 in]

Impedance: 75Ω

RF Connector Coupling Mechanism: Bayonet

Features

Product Type Features

RF Interface	BNC
RF Connector Style	Jack
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

PCB Mount Orientation	Vertical
Number of Positions	1
Number of Coaxial Contacts	1

Electrical Characteristics

Impedance	75 Ω	

Body Features

Body Material	Zinc
Body Plating Material	Tin

Contact Features



	1080 µin
RF Connector Center Contact Plating Material	Gold (Au)
RF Connector Center Contact Material	Phosphor Bronze
Termination Features	
Termination Method to PCB	Through Hole - Solder
Termination Post & Tail Length	4.44 mm[.175 in]
Mechanical Attachment	
PCB Mount Retention	Without
RF Connector Coupling Mechanism	Bayonet
Connector Mounting Type	Panel Mount
RF Contact Captivation Method	Mechanical
Detent	With
Dimensions	
Dimensions Profile Height from PCB	16.64 mm[.655 in]
	16.64 mm[.655 in] 14.53 mm[.572 in]
Profile Height from PCB	
Profile Height from PCB RF Connector Mated Outer Diameter (Approximate)	
Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions	14.53 mm[.572 in]
Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option	14.53 mm[.572 in]
Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Operation/Application	14.53 mm[.572 in] Uninsulated
Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Operation/Application Operating Frequency	14.53 mm[.572 in] Uninsulated
Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Operation/Application Operating Frequency Packaging Features	14.53 mm[.572 in] Uninsulated 4 GHz
Profile Height from PCB RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Operation/Application Operating Frequency Packaging Features Packaging Method	14.53 mm[.572 in] Uninsulated 4 GHz

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)



Candidate List Declared Against: JUNE

2024 (241)

SVHC > Threshold:

Pb (4% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free

Solder Process Capability

Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | OEG Miniature Relay PCF



Combo Jacks(1)




Connector Contacts(1)



Power Contacts(1)



RJ14 Connectors(1)



Customers Also Bought























Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5414394-1_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5414394-1_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5414394-1_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

BNC Connectors

English