

KUP-5D15-12

✓ ACTIVE

Potter & Brumfield | Potter & Brumfield KUP

TE Internal #: 6-1393118-6

General Purpose Power Relay, DC, Monostable, 1 Form C SPDT-CO, 10 A Contact Rating, 12 VDC Coil Voltage, Potter & Brumfield KUP

[View on TE.com >](#)



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: **General Purpose Power Relay**

Current Type: **DC**

Coil Magnetic System: **Monostable**

Contact Arrangement: **1 Form C SPDT-CO**

Contact Current Rating: **10 A**

Features

Product Type Features

Relay & Contactor Type	General Purpose Power Relay
------------------------	-----------------------------

Configuration Features

Contact Number of Poles	1
Coil Special Features	UL Coil Insulation Class B
Contact Arrangement	1 Form C SPDT-CO

Electrical Characteristics

Contact Limiting Short-Time Current	10 A
Contact Limiting Making Current	10 A
Contact Limiting Continuous Current	10 A
Contact Limiting Breaking Current	10 A
Insulation Initial Dielectric Between Open Contacts	1200 Vrms
Insulation Initial Dielectric Between Adjacent Contacts	2200 Vrms
Contact Switching Load (Min)	300mA @ 12V
Coil Resistance	120 Ω
Insulation Initial Resistance	100 MΩ
Contact Current Rating	10 A
Coil Voltage Rating	12 VDC
Contact Voltage Rating	240 VAC



Coil Power Rating DC	1.2 W
Insulation Initial Dielectric Between Contacts & Coil	2200 Vrms

Body Features

Product Weight	85 g[2.988 oz]
Enclosure Type	Dust Protected

Contact Features

Contact Material	Silver Cadmium Oxide
------------------	----------------------

Termination Features

Main Termination & Connection Type	Quick Connect Terminals
Coil Termination & Connection Type	Quick Connect Terminals

Mechanical Attachment

Product Mount Type	Panel & Socket Mount
--------------------	----------------------

Dimensions

Product Width	35.71 mm[1.4 in]
Product Length	38.89 mm[1.53 in]
Product Height	49.2 mm[1.93 in]

Usage Conditions

Operating Temperature Range	-45 – 70 °C[-49 – 158 °F]
Environmental Category of Protection	RTI
Environmental Ambient Temperature (Max)	70 °C[158 °F]

Operation/Application

Current Type	DC
Coil Magnetic System	Monostable

Packaging Features

Packaging Method	Package
------------------	---------

Other

Coil Power Rating Class	1 – 1.5 W
Contact Current Class	16 A
Environmental Ambient Temperature Class	50 – 70 °C
Height Class (Mechanical)	40 – 50 mm
Length Class (Mechanical)	35 – 40 mm



Width Class (Mechanical)

30 – 40 mm

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Cadmium oxide (4.37% in Component part) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2-1419106-2
27E867=SOCKET,KU,,ASSY,4 POLE,

TE Part # 4-1393143-0
27E419=SOCKET,KU,14, HARDMOUNT,PCB

TE Part # 7-1393118-0
KUP-5D55-12=KU

Also in the Series | Potter & Brumfield KUP

A collection of various AC relays, including a large white one with multiple pins and several smaller black ones.

AC Relays(31)

A collection of various DC relays, including a large silver one and several smaller black ones.

DC Relays(35)

A collection of various electromechanical relays, including a large black one and several smaller ones in different colors.

Electromechanical Relays(66)

A collection of various plug-in relays, including a large black one and several smaller ones in different colors.

Plug-In Relays(66)

A collection of various relay accessories, including a large white one and several smaller ones in different colors.

Relay Accessories(10)

Customers Also Bought

A large, rectangular, black plastic component with many pins.

TE Part #206800-2
PLG ASSY,25 POS,AMPLIMITE

A small, black, rectangular component with pins.

TE Part #3-1393159-9
20C254=SPRING,HOLD-DOWN,KUP,0

A small, black, rectangular component with pins.

TE Part #4-1393117-4
KUP-11D15-12=KU

A small, black, rectangular component with pins.

TE Part #1-1622796-1
YR1 0.1% 16K2

A large, rectangular, black plastic component with many pins.

TE Part #207252-2
PLUG ASSY,SZ 1,AMPLIMITE

A small, black, rectangular component with pins.

TE Part #4-1393117-5
KUP-11D15-24=KU

A long, black, rectangular component with many pins.

TE Part #3-1546306-0
30P.374" DR BARRIER STRIP

A small, black, rectangular component with pins.

TE Part #4-1393253-3
W68-X2Q13-15=M6/M7/M9/W6/W7

A small, black, rectangular component with pins.

TE Part #7-1622796-3
YR1 0.1% 169K

A small, black, rectangular component with pins.

TE Part #1393255-8
W93-X112-30=M6/M7/M9/W6/W7

Documents



CAD Files

Customer View Model

ENG_CVM_CVM_6-1393118-6_D.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-1393118-6_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-1393118-6_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

KU Sockets & Accessories

English

KUP Series Panel Plug-in Relay

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

UL

English