6-1437649-7 ACTIVE

Buchanan

TE Internal #: 6-1437649-7


8 Position Barrier Strip, Tri-Barrier, Solderless Wire Wrap Bottom Termination, Wire-to-Board, 8.26 mm [.325 in] Centerline, 1 Row,

150 V / 300 V

View on TE.com >



Connectors > Terminal Blocks & Strips > Barrier Strips











Number of Positions: 8

Barrier Strip Style: Tri-Barrier

Bottom Termination Type: Solderless Wire Wrap

Connector System: Wire-to-Board
Centerline (Pitch): 8.26 mm [.325 in]

Features

Product Type Features

Treader Type I edianes	
Block Style	Flat Bottom with standoffs
Connector System	Wire-to-Board
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Levels	1
Number of Positions	8
Number of Rows	1
Electrical Characteristics	
Operating Voltage	150 V, 300 V
Body Features	
Primary Product Color	Black
Product Orientation	Vertical
Barrier Strip Style	Tri-Barrier



Contact Features

Contact Base Material	Copper Alloy
PCB Contact Termination Area Plating Material	Tin
Contact Current Rating (Max)	20 A

Termination Features

Mechanical Attachment

Top Termination Type	Wire Clamp Combo Head
Mounting Options	End Positions with Inserts
Screw Plating Material	Zinc
Screw Material	Steel
Thread Size	4-40
Screw Head Type	Combo Phil-Slot
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	Polyamide
Centerline (Pitch)	8.26 mm[.325 in]

Dimensions

Product Length	84.07 mm[3.311 in]
Wire Size	22 – 14 AWG

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Packaging Features

Packaging Method	Package
Packaging Quantity	85

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Customers Also Bought















Documents

Product Drawings
4WWV-08-442=PP, MTG HOLES FOXB



English

CAD Files

Customer View Model

ENG_CVM_CVM_6-1437649-7_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-1437649-7_G.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_6-1437649-7_G.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

BUCHANAN TERMINAL BLOCKS CATALOG - BARRIER STRIPS

English