

Nanonics

TE Internal #: 6-1589483-0

51 Position D-Shaped Connector, Receptacle, Wire-to-Board,


Board Mount, .64 mm [.025 in] Centerline, Printed Circuit Board,

Power

View on TE.com >



Connectors > D-Shaped Connectors > DUALOBE Receptacle Connectors: Metal Shell, 51 Pin/2 row



Number of Positions: 51

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Connector Mounting Type: Board Mount

Centerline (Pitch): .64 mm [.025 in]

All DUALOBE Receptacle Connectors: Metal Shell, 51 Pin/2 row (9)

Features

Product Type Features

Sealable	No
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Contact Features

Contact Type	Socket
Contact Current Rating (Max)	1 A
Contact Options	Installed

Termination Features

Termination Method to PCB	Surface Mount
Termination Method to Wire & Cable	Preterminated Flying Leads
Mechanical Attachment	
Connector Mounting Type	Board Mount

Housing Features



Centerline (Pitch)	.64 mm[.025 in]
Usage Conditions	
Operating Temperature Range	-200 – 200 °C[-328 – 392 °F]
Operation/Application	
Circuit Application	Power

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (40% in 74023047) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1589666-5 302-0009-02 = CLEADFRAME

Customers Also Bought






















Documents

Product Drawings
STM051L2AQ = SMT CONN

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-1589483-0_U_c-6-1589483-0-u.2d_dxf.zip

51 Position D-Shaped Connector, Receptacle, Wire-to-Board, Board Mount, .64 mm [. 025 in] Centerline, Printed Circuit Board, Power



English

Customer View Model

ENG_CVM_CVM_6-1589483-0_U_c-6-1589483-0-u.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-1589483-0_U_c-6-1589483-0-u.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1589483 Nanonics Cross Reference

English