

M12 Connector

TE Internal #: 6-2271122-2

12 Position Circular Connector, Cable-to-Cable, Sealable, Wire &

Cable, Signal, Reverse Gender, Nickel, Zinc Alloy, A Code, PA, M12

Connector

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Number of Positions: 12

Connector System: Cable-to-Cable

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Contact Current Rating (Max): 2A

Features

Factory Installed Backshell

Number of Positions

| Product Type Features | |
|---------------------------------------|----------------------|
| Assembly Requirement | Factory Assembled |
| Circular Connector Shell Type | Metal-Shell |
| Connector Product Type | Connector Assembly |
| Assembly Type | Electrical Connector |
| Prewired | No |
| Connector System | Cable-to-Cable |
| Sealable | Yes |
| Connector & Contact Terminates To | Wire & Cable |
| Circular Connector Type | Plug |
| Shell Type | Metal |
| Configuration Features | |
| Keying & Polarized Position Locations | A |

With

12



| Number of Power Positions | 0 |
|---|---------------------------|
| Number of Signal Positions | 12 |
| Contacts Preloaded | Yes |
| Body Features | |
| Environmental Protection | IP67 |
| Environmental Protection Type | Sealed |
| Primary Product Color | Metalized Silver |
| Shell Plating Material | Nickel |
| Shell Base Material | Zinc Alloy |
| Circular Connector Insulation Material Type | PA |
| Hermetically Sealed | Yes |
| Contact Features | |
| Contact Current Rating (Max) | 2 A |
| Reverse Gender | Yes |
| Circular Connector Contact Type | Pin |
| Termination Features | |
| Termination Method to Wire & Cable | Solder |
| Mechanical Attachment | |
| Mating Retention Type | Threaded |
| Mating Alignment | With |
| Polarization Code | A |
| Mating Alignment Type | Keyed |
| Mating Retention | With |
| Housing Features | |
| Circular Connector Shell Size | 20 |
| Dimensions | |
| Wire Size | 26 – 24 AWG |
| Usage Conditions | |
| IP Dust Sealing Level | 6 |
| IP Water Sealing Level | IP67 |
| Operating Temperature Range | -40 - 85 °C[-40 - 185 °F] |
| | |



| Circuit Application | Signal |
|---|--------|
| Shielded | No |
| Industry Standards | |
| Compatible With Approved Standards Products | IEC |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant with Exemptions |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






Also in the Series | M12 Connector









Customers Also Bought













Documents

Product Drawings

M12, MALE, A CODE, R/A, 12P, PG9 (AU)

English

CAD Files

3D PDF

3D

12 Position Circular Connector, Cable-to-Cable, Sealable, Wire & Cable, Signal, Reverse Gender, Nickel, Zinc Alloy, A Code, PA, M12 Connector



Customer View Model

ENG_CVM_CVM_6-2271122-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-2271122-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-2271122-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

Product Specifications

Product Specification

English