# 603502-2 - ACTIVE

TE Internal #: 603502-2 Butt Splice, 22 – 18 AWG, .3 – .9 mm<sup>2</sup> Wire, Sealable, 509 – 1900 CMA, Copper, Red, 43 mm [1.693 in] Length, Loose Piece, Closed Barrel, Stranded Wire

#### View on TE.com >

Terminals & Splices > Splices



Splice Type: Butt Splice

Wire Size: .3 – .9 mm<sup>2</sup>

Sealable: Yes

Compatible Insulation Diameter Range: 4.32 mm [.17 in ]

### Features

#### **Product Type Features**



Splice Type	Butt Splice						
Sealable	Yes						
Compatible With Discrete Wire Type	Stranded						
Wire Insulation Support Retention Type	Insulation Support						
Configuration Features							
Compatible With Wire & Cable Type	Discrete Wire						
Electrical Characteristics							
Operating Voltage	600 V						
Body Features							
	.003 oz						
Insulation Material	Nylon						
Insulation Type	Pre-Insulated						
Primary Product Color	Red						
Contact Features							
Terminal Plating Material	Tin						

#### 603502-2

Butt Splice, 22 – 18 AWG, .3 – .9 mm<sup>2</sup> Wire, Sealable, 509 – 1900 CMA, Copper, Red, 43 mm [1.693 in] Length, Loose Piece, Closed Barrel, Stranded Wire



Contact Base Material	Copper
Barrel Type	Closed
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Recovered Inside Diameter	1.65 mm[.065 in]
Outside Diameter	4.45 mm[.175 in]
Wire Size	509 – 1900 CMA
Compatible Insulation Diameter Range	4.32 mm[.17 in]
Barrel Inside Diameter	4.32 mm[.17 in]
Product Length	43 mm[1.693 in]
Usage Conditions	
Insulation Option	Fully Insulated
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Industry Standards	
Government Qualified Splice	No
De des sites - Es sterres	

#### Packaging Features

Packaging Quantity

Packaging Method

Product Compliance

Loose Piece

50

For compliance documentation, visit the product page on TE.com>				
EU RoHS Directive 2011/65/EU	Compliant			
EU ELV Directive 2000/53/EC	Compliant			
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold			
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC			
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free			
Solder Process Capability	Not applicable for solder process capability			

**C** For support call+1 800 522 6752

#### 603502-2

Butt Splice, 22 – 18 AWG, .3 – .9 mm<sup>2</sup> Wire, Sealable, 509 – 1900 CMA, Copper, Red, 43 mm [1.693 in] Length, Loose Piece, Closed Barrel, Stranded Wire



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Customers Also Bought**



An -TE	= TE	= TE	TE	
TE Part #1-1825059-1 ADF03ST04=DIP SWT,FLUSH,SMT-GW	TE Part #33115-1 TERMINAL,SOLIS R 4 5/16 90DEG	TE Part #35668 TERMINAL,SOLIS R 4 1/2	TE Part #5745967-2 25 RCPT SP/FMS STD	



### Documents

Product Drawings PRE-INSUL SEALED SPLICE 22-16

English

CAD Files 3D PDF

#### 603502-2

Butt Splice, 22 – 18 AWG, .3 – .9 mm<sup>2</sup> Wire, Sealable, 509 – 1900 CMA, Copper, Red, 43 mm [1.693 in] Length, Loose Piece, Closed Barrel, Stranded Wire



3D

Customer View Model ENG\_CVM\_CVM\_603502-2\_K.2d\_dxf.zip English Customer View Model ENG\_CVM\_CVM\_603502-2\_K.3d\_igs.zip English Customer View Model ENG\_CVM\_CVM\_603502-2\_K.3d\_stp.zip English Customer View Model ENG\_CVM\_603502-2\_N.3d\_igs.zip English **Customer View Model** ENG\_CVM\_603502-2\_N.3d\_stp.zip English **Customer View Model** ENG\_CVM\_603502-2\_N.2d\_dxf.zip English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.