




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **642 – 1624 CMA**

Mating Tab Width: **2.8 mm [.11 in]**

Features

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------



Mating Retention Type

Dimple

Dimensions

Terminal Material Thickness	.25 mm[.01 in]
Wire Size	642 – 1624 CMA

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	15000
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts




KIT

REPRESENTATION ONLY

TE Part # 7-2150636-7
[OCEAN_2.0_SPARE_PART_KIT-062F090OV](#)




TE Part # 2150049-2
[OCEAN-2.0-APPLICATOR-E-062F090FA-REA](#)



TE Part # 2150049-1
[OCEAN-2.0-APPLICATOR-E-062F090F-REM](#)



TE Part # 2150636-1
[OCEAN-2.0-APPLICATOR-E-062F090OV-REM](#)



KIT

REPRESENTATION ONLY

TE Part # 7-2150049-7
[OCEAN_2.0_SPARE_PART_KIT-062F090F](#)




TE Part # 2063846-1
[CCII 110 FASTON REC 24-18 ASSY](#)



TE Part # 2150636-2
[OCEAN-2.0-APPLICATOR-E-062F090OV-REA](#)

Also in the Series | **FASTON 110**



[Crimp Terminal Housings\(13\)](#)



[Insertion & Extraction Tools\(1\)](#)



[PCB Terminals\(22\)](#)




[Quick Disconnects\(164\)](#)

Customers Also Bought



TE Part #EG8105-000
[VERSAFIT-1/4-0-15MM](#)



TE Part #1478484-1
[STATOR TERMINAL](#)



TE Part #4862984002
[CGPE-105-3/8-0-SP](#)




TE Part #626028-4
[RING TONGUE TERMINAL](#)






TE Part #2-33460-2
[TERMINAL,SOLIS R 8 10](#)



TE Part #1742451-1
[AMPLIVAR WIRE PIN 600-1400 020BRS](#)



TE Part #60197-2
[110 FASTON REC 22-18 AWG BR](#)



TE Part #1478484-2
[STATOR TERMINAL](#)



TE Part #1879071-7
[THS50 R33 5%](#)



TE Part #796740-3
[3 POS PCB MT 6.35MM HI CRT TBK](#)

Documents

Product Drawings

[110 FASTON REC 22-18 AWG TPBR](#)

English

CAD Files

Customer View Model

[ENG_CVM_CVM_60577-1_P.2d_dxf.zip](#)

English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_60577-1_P.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_60577-1_P.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[82004 FASTON Terminals \(Insulated and Uninsulated\) Catalog - FASTON Receptacles Section](#)

English

Product Specifications

[Application Specification](#)

English

Agency Approvals

[UL Report](#)

60577-1

Quick Disconnect Receptacle, 22 – 18 AWG, .32 – .82 mm² Wire, 642 – 1624 CMA, 2.8 mm [.11 in] Tab Width, Straight, Brass, Tin Plating, FASTON 110



English