



Terminals & Splices > PCB Terminals



PCB Terminal Type: **Receptacle**

PCB Thickness (Recommended): **1.6 – 2.39 mm [.063 – .094 in]**

PCB Hole Diameter: **3.68 mm [.145 in]**

Mating Pin Diameter: **1.47 mm [.058 in]**

Profile Height from PCB: **5.33 mm [.212 in]**

Features

Product Type Features

Terminal Features	Stud Hole
-------------------	-----------

Contact Features

PCB Contact Termination Area Plating Material Thickness	3.81 μm[150 μin]
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
PCB Terminal Type	Receptacle
Mating Pin Diameter	1.47 mm[.058 in]
Terminal Plating Material	Gold
Contact Underplating Material	Nickel
Terminal Orientation	Straight

Termination Features

Termination Method to PCB	Through Hole - Press-Fit
Product Terminates To	Printed Circuit Board

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------



Dimensions

Extension Below Board	3.81 mm[.15 in]
Terminal Material Thickness	.25 mm[.01 in]
PCB Thickness (Recommended)	1.6 – 2.39 mm[.063 – .094 in]
PCB Hole Diameter	3.68 mm[.145 in]
Profile Height from PCB	5.33 mm[.212 in]

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Customers Also Bought



TE Part #1614352-1
RN 0603 20K 0.1% 10PPM 5K RL

TE Part #1-284511-6
16 POS TERMI-BLOK PLUG C. VITI

TE Part #1623722-4
SBCH 11 33R 5%

TE Part #2-1393203-8
V23148-A1007-A101

TE Part #1614353-4
RN 0603 2K37 0.1% 10PPM CUT LENGTH

TE Part #1614353-9
RN 0603 2K67 0.1% 10PPM CUT LENGTH

TE Part #1775284-3
HPI, 2.5MM, EMIX, A'SSY, V/T, 3P, IVORY

TE Part #5415633-1
RTANG BNC PCB JACK - 75 OHM

TE Part #1-1542001-2
HTS264NF-D=HS ASSY PPA CLIP

TE Part #1825013-6
MRD10CSTR04=7MM ROT DIP, BCD COMP

Documents

Product Drawings

[.058 DIA PIN PC AUSNPB/NI/PHBZ](#)

English

CAD Files

Customer View Model

[ENG_CVM_60803-1_AJ1.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_60803-1_AJ1.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_60803-1_AJ1.2d_dxf.zip](#)

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications



Application Specification

English