#### **AMP-IN**

TE Internal #: 60874-1

Receptacle, 4.5 mm [.177 in] PCB Hole, Through Hole - Press-Fit, Pre-Tin Plating, Bag, Terminates To Printed Circuit Board, Straight,

PCB Terminals

View on TE.com >



Terminals & Splices > PCB Terminals











PCB Terminal Type: Receptacle

PCB Thickness (Recommended): 1.6 – 2.39 mm [ .063 – .094 in ]

PCB Hole Diameter: 4.5 mm [.177 in]

Mating Pin Diameter: 1.47 mm [.058 in]

Profile Height from PCB: 5.33 mm [.212 in]

## Features

## **Product Type Features**

Terminal Features	Stud Hole
Contact Features	
PCB Terminal Type	Receptacle
Mating Pin Diameter	1.47 mm[.058 in]
Terminal Plating Material	Pre-Tin
Terminal Size	Miniature
Terminal Orientation	Straight
Termination Features	
Termination Method to PCB	Through Hole - Press-Fit
Product Terminates To	Printed Circuit Board
Mechanical Attachment	
Wire Insulation Support	Without

**Dimensions** 



Extension Below Board	3.81 mm[.15 in]
Terminal Material Thickness	.25 mm[.01 in]
PCB Thickness (Recommended)	1.6 – 2.39 mm[.063 – .094 in]
PCB Hole Diameter	4.5 mm[.177 in]
Profile Height from PCB	5.33 mm[.212 in]

### **Usage Conditions**

Insulation Option	Uninsulated
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

#### **Packaging Features**

Packaging Quantity	1000
Packaging Method	Bag

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# Compatible Parts







# Customers Also Bought





















## **Documents**

Product Drawings
.058 PCB PIN PTPPHBZ

English

CAD Files
3D PDF

3D



**Customer View Model** 

ENG\_CVM\_60874-1\_D.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_60874-1\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_60874-1\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

## Datasheets & Catalog Pages

PRINTED CIRCUIT BOARD TERMINALS AND DISCONNECTS

English

**Product Specifications** 

**Application Specification** 

English