




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **1.31 – 3.31 mm²**

Mating Tab Width: **7.92 mm [.312 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	7.92 mm[.312 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	20.86 mm[.9 in]
Compatible Insulation Diameter Range	2.79 – 5.33 mm[.11 – .21 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	1.31 – 3.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	6000
Packaging Method	Strip/Reel

Other

Line	Premier
------	---------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



KIT

REPRESENTATION ONLY


TE Part # 7-2150176-7
[OCEAN_2.0_SPARE_PART_KIT-120F250F](#)



TE

TE Part # 2150176-2
[OCEAN_2.0_Applicator-E-120F250F-REA](#)

Also in the Series | FASTON 312



[Crimp Terminal Housings\(3\)](#)



[PCB Terminals\(1\)](#)



[Quick Disconnects\(8\)](#)

Customers Also Bought



TE Part #520988-1
[ULTRA-POD 250 ASSY REC 22-18 AWG BR](#)



TE Part #521411-1
[ULTRA-POD 250 ASY REC 22-18 AWG BR](#)




TE Part #1-770849-5
[15P SL156 HSG W/LOC RAMP W/TBS](#)



TE Part #42800-1
[187 FASTON REC 20-16 AWG BR](#)






TE Part #63435-1

250 FASTON REC 14-10 AWG SPBR




TE Part #521282-2

ULTRA-POD 250 ASSY REC 18-14 AWG TPBR



TE Part #1-480487-2

FASTON 187 FLAG HSG NYLON NAT LP



TE Part #640748-7

HEAVY DUTY BURNER REC 18-14 AWG PHBRZ



TE Part #61769-1

SPLICE 1200-2600 .020 BR

TE Part #1-521204-7

HSG, POS LOCK, .250 SERIES, 2 POSITION

Documents

Product Drawings

312 FASTON REC 16-12 AWG TPBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_61399-1_W.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_61399-1_W.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_61399-1_W.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Engineering Report

English

Agency Approvals

UL

61399-1

Quick Disconnect Receptacle, 16 – 12 AWG, 1.31 – 3.31 mm² Wire, 7.92 mm [.312 in]
Tab Width, Straight, Brass, Tin Plating, Strip/Reel, FASTON 312



English