




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

--	--



Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	17.14 mm[.675 in]
Compatible Insulation Diameter Range	3.05 – 3.81 mm[.12 – .15 in]
Terminal Material Thickness	.81 mm[.032 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Packaging Features

Packaging Quantity	3500
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2266314-2
OCEAN_2.0_Applicator-S-110F180O-RSA

TE Part # 63919-1
187 FASTON TAB 18-14 AWG TPBR

TE Part # 2305570-1
Strip Terminal Cutter-Side Feed-No Crimp

TE Part # 61367-3
250 FASTON TAB 18-14 AWG TPBR

TE Part # 7-2266314-7
OCEAN_2.0_SPARE_PART_KIT-110F180O

TE Part # 2266314-1
OCEAN_2.0_Applicator-S-110F180O-RSM

Also in the Series | FASTON 187

Crimp Terminal Housings(40)

Insertion & Extraction Tools(1)

Insulation Boots & Sleeves(1)

Joints & Splices(1)

PCB Terminals(42)

Quick Disconnects(205)

Splices(1)

Customers Also Bought



TE Part #160780-4
110 FASTON, REC., 16-20 AWG, TPBR

TE Part #1-292228-2
1.5 MINI CT SGL H SMT W/O BOSS

TE Part #292254-6
CT RELAY HDR ASSY 6P NAT

TE Part #384456-E
SRCBUG A 2,54 2 4 CSI 165 E1 ADV J 2 324

TE Part #61831-1
WING TYPE STRAIN RELIEF TPST

TE Part #1742800-1
FF 187 TAB 18-14AWG TPBR

TE Part #1745000-3
8POS MQS REC

TE Part #353293-3
MINI CT MT REC ASSY 3P GRAY

TE Part #58583-1
PROCRIMP HT&D SUPRSEAL 1.5 SER

TE Part #175063-1
040 MULTILOCK TAB CONT. L/P

Documents

Product Drawings
187 FASTON TAB 18-14 AWG TPBR
English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_61687-2_U.2d_dxf.zip
English
Customer View Model
ENG_CVM_CVM_61687-2_U.3d_igs.zip
English
Customer View Model
ENG_CVM_CVM_61687-2_U.3d_stp.zip
English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



FASTON Tabs

English

Agency Approvals

UL Report

English