

TE Internal #: 62244-3

Receptacle, 18 – 16 AWG Lead Wire, .82 – 1.3 mm² Lead Wire, Crimp, 4.32 mm [.17 in] Crimp Area Length, Tin Plating, Magnet

Wire Terminals

View on TE.com >



Terminals & Splices > Magnet Wire Terminals











Magnet Wire Terminal Type: Receptacle

Mating Pin Diameter: 3.18 mm [.125 in]

Compatible Insulation Diameter (Max): 3.3 mm [.13 in]

Compatible Insulation Diameter Range: 2.3 – 3.3 mm [.09 – .13 in]

Lead Wire Size: .82 – 1.3 mm²

Features

Product Type Features

Wire Insulation Support Retention Type	Insulation Support
Compatible With Discrete Wire Type	Lead Wire, Stranded
Contact Features	
Crimp Type	F-Crimp

Crimp Type	F-Crimp
Magnet Wire Terminal Type	Receptacle
Mating Pin Diameter	3.18 mm[.125 in]
Terminal Plating Material	Tin
Terminal Orientation	Straight

Termination Features

Termination Method to Wire & Cable	Crimp
Crimp Area Length	4.32 mm[.17 in]

Mechanical Attachment

Wire Insulation Support	With	
-------------------------	------	--

Dimensions



Terminal Height	6.1 mm[.24 in]
Compatible Insulation Diameter (Max)	3.3 mm[.13 in]
Compatible Insulation Diameter Range	2.3 – 3.3 mm[.09 – .13 in]
Lead Wire Size	18 – 16 AWG
Stock Thickness (Magnet Wire Side)	.51 mm[.02 in]
Product Length	20.96 mm[.825 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-20 - 105 °C[-4 - 221 °F]
Operation/Application	
Compatible With Wire Base Material	Copper

9000

Package

Product Compliance

Packaging Quantity

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



















Customers Also Bought























Documents

Product Drawings

125 PIN RCPT 18-16

English

CAD Files

Customer View Model

ENG_CVM_CVM_62244-3_AG.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_62244-3_AG.3d_igs.zip

English

Customer View Model

ENG_CVM_62244-3_AG.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Magnet Wire Terminals & Splices

English

Product Specifications

Application Specification

English