### **SPLICE**

TE Internal #: 62419-3

Pigtail Splice, 18 – 14 AWG, .8 – 2 mm<sup>2</sup> Wire, 2 Splice Capacity, Serrated, 1600 – 4100 CMA, Steel, 3 / 4 Serration, 17.9 mm [.705 in]

Length, SPLICE

View on TE.com >



Terminals & Splices > Splices











Splice Type: Pigtail Splice

Wire Size: .8 – 2 mm²

Sealable: No

Splice Capacity: 2

# **Features**

# Product Type Features

Splice Type	Pigtail Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Insulation Support

# **Configuration Features**

Strip Orientation	End Feed
Splice Capacity	2
Number of Serrations	3, 4
Compatible With Wire & Cable Type	Discrete Wire

# **Electrical Characteristics**

Operating Vo	oltage	250 V
--------------	--------	-------

# **Body Features**

Product Weight	.459 g
Splice Features	Serrated



## **Contact Features**

Terminal Plating Material	Nickel
Contact Base Material	Steel
Barrel Type	Open
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	1600 – 4100 CMA
Compatible Insulation Diameter Range	4.32 mm[.17 in]
Terminal Material Thickness	.51 mm[.02 in]
Product Length	17.9 mm[.705 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 – 250 °C[-40 – 482 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	3000

# **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Strip



#### Free

#### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**







# Also in the Series | SPLICE







# Customers Also Bought






















TE Part #8-1423022-1 W57-XD1A8B20-15=CKTBKR,THERM, PB,QC.250,B

## **Documents**

## **Product Drawings**

SPLICE 18-16/18-14 AWG .020 NPST

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_62419-3\_R.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_62419-3\_R.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_62419-3\_R.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# **Product Specifications**

**Product Specification** 

English