

#### **SPLICE**

TE Internal #: 63130-2

Pigtail Splice / Thru Splice, Serrated, 1500 – 5000 CMA, Brass, 3 Serration, 8.26 mm [.325 in] Length, Reel, Open Barrel, SPLICE

View on TE.com >



Terminals & Splices > Splices











Splice Type: Pigtail Splice, Thru Splice

Sealable: No

Splice Features: Serrated
Wire Size: 1500 – 5000 CMA
Contact Base Material: Brass

### **Features**

### Product Type Features

Splice Type	Pigtail Splice, Thru Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Number of Serrations	3
Compatible With Wire & Cable Type	Discrete Wire
Compatible With Wire & Cable Type  Body Features	Discrete Wire
	Discrete Wire .151 g
Body Features	
Body Features  Product Weight	.151 g

Open

Barrel Type

Mechanical Attachment



Wire Insulation Support	Without
Dimensions	
Wire Size	1500 – 5000 CMA
Terminal Material Thickness	.51 mm[.02 in]
Product Length	8.26 mm[.325 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	7500
Packaging Method	Reel

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**
















# Also in the Series | SPLICE





## Customers Also Bought













TE Part #62754-1 SPLICE 14000-30000 .030 BR



TE Part #62759-1 SPLICE 400-1300 .016 BR



TE Part #CAT-UL8-25021 ULTRA POD: Flag, Receptacle Assembly, Tin Plated, .250 inch



TE Part #1428057-1 CIRCUIT BREAKER,MAGNETIC

### **Documents**

### **Product Drawings**

SPLICE REC. 1500-5000 .020 BR

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_63130-2\_AD.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_63130-2\_AD.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_63130-2\_AD.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Product Specifications**

**Application Specification** 

English

### **Agency Approvals**

**UL Report** 

English