

TE Internal #: 6364666-2

Board-to-Board Card Edge Power Connector, 50 Position, 2.54 mm

[.1 in] Centerline, Power & Signal, 50 Power Positions, 0 Signal

Positions

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > Card Edge Power Connectors



Connector System: Board-to-Board

Number of Positions: 50

Centerline (Pitch): 2.54 mm [.1 in]

Contact Current Rating (Max): 4.26 A

Circuit Application: Power & Signal

Features

Product Type Features

Connector & Contact Terminates To	Printed Circuit Board
Connector Mates With	Printed Circuit Board
Connector & Housing Type	Receptacle
Connector System	Board-to-Board
Configuration Features	
Keying & Polarized Position Locations	11, 12
PCB Mount Orientation	Vertical
Number of Positions	50
Number of Power Positions	50
Number of Signal Positions	0
Number of Dual Positions	25

400 V

Body Features

Electrical Characteristics

Operating Voltage



Primary Product Color	Black
Contact Features	
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material Finish	Matte
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
PCB Contact Termination Area Plating Material Thickness	2.54 μm[100 μin]
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
Contact Type	Socket
Contact Current Rating (Max)	4.26 A
Contact Mating Area Plating Material	Gold (Au)
Termination Features	
Termination Post & Tail Length	3.18 mm[.125 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Connector Mounting Type	Board Mount
Mating Retention Type	Latch
PCB Mount Retention	With
Mating Retention	With
PCB Mount Retention Type	Action/Compliant Tail
Mating Alignment Type	Keyed
Mating Alignment	With
PCB Mount Alignment	Without
Housing Features	
Housing Material	Polyester GF
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Card Slot Depth	7.63 mm[.309 in]
Row-to-Row Spacing	4.85 mm[.191 in]
Connector Height	15.63 mm[.75 in]
Power Contact Centerline	2.54 mm[.1 in]
Usage Conditions	



Operating Temperature Range	-55 – 90 °C[-67 – 194 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	6
Packaging Method	Box
Other	
Position Locations Omitted	44

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought



















Documents

Product Drawings

CONN SEC II 25 POS W/ LATCH

English

CAD Files

Customer View Model ENG_CVM_6364666-2_D.3d_igs.zip

English

Customer View Model

Board-to-Board Card Edge Power Connector, 50 Position, 2.54 mm [.1 in] Centerline, Power & Signal, 50 Power Positions, 0 Signal Positions



ENG_CVM_6364666-2_D.3d_stp.zip

English

Customer View Model

ENG_CVM_6364666-2_D.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English