




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Compatible Insulation Diameter Range	2.16 – 3.43 mm[.085 – .135 in]
Terminal Material Thickness	.3 mm[.012 in]
Wire Size	.51 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	12000
Packaging Method	Strip/Reel

Other

Line	Budget
------	--------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 180363-1 250 FASTON,REC.,12-10 AWG,BR	 TE Part # 160808-2 250 FASTON,REC.,17-14 AWG,BR	 TE Part # 5-160432-3 250 FASTON REC 20-16 AWG BR	 TE Part # 2-160256-1 250 FASTON,REC.,17-14 AWG,BR
 TE Part # 41202-1 250 FASTON,REC.,18-14 AWG,BR	 TE Part # 150645-2 250 FASTON,REC.,18-14 AWG,BR	 TE Part # 1-280001-1 250 FASTON,REC.,14-17 AWG,BR	 TE Part # 342368-1 187 FASTON,REC.,30-24 AWG,BR
 TE Part # 170183-1 250 FASTON,REC.,22-18 AWG,BR	 TE Part # 160807-2 250 FASTON,REC.,20-16 AWG,BR		

Also in the Series | FASTON 250




Compression Connectors(4)



Crimp Terminal Housings(116)



Insulation Boots & Sleeves(16)



Magnet Wire Terminals(1)



PCB Terminals(134)



Quick Disconnects(421)



Splices(4)

Customers Also Bought



TE Part #1-176271-1
AMP UNIVERSAL POWER PLUG 2P




TE Part #2-5176837-1
44 AMPMODU 2MM, H, AU, LF



TE Part #1-794075-1
16P MINI UMNL HDR W/O DH AU LF



TE Part #5227726-1
ISOLATED BNC SOLDER JACK ASSY



TE Part #1SNK508060R0000
ZS10-YL



TE Part #3-647477-3
03P MTA100 CONN ASSY F/T LF




TE Part #1742999-1
250 FASTON, FLAG, REC., 18-14 AWG, BR



TE Part #1-640456-0
10P MTA100 HDR ASSY F/L SQ STR



TE Part #350654-7
UMNL GROUNDING PIN AUBR



TE Part #1744001-3
03P MTA156 HDR POL .045SQ TIN

Documents



Product Drawings

250 FASTON FLAG REC 20-14 AWG BR

English

CAD Files

Customer View Model

ENG_CVM_CVM_63648-1_L.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63648-1_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_63648-1_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English