



Connectors > Contacts > Connector Contacts



Contact Type: **Socket**
Contact Mating Area Plating Material: **Tin (Sn)**
Wire Contact Termination Area Plating Material: **Tin**
Operating Voltage: **250 VDC**

Features

Product Type Features

Discrete Wire Type	Stranded
Sealable	No

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Electrical Characteristics

Operating Voltage	250 VDC
-------------------	---------

Contact Features

Contact Orientation	Straight
Mating Pin Diameter	1.98 mm[.077 in]
Contact Fabrication	Stamped & Formed
Contact Mating Area Plating Material Thickness	.4 µm[15.75 µin]
Contact Length	16.76 mm[.66 in]
Wire Contact Termination Area Plating Thickness	.4 µm[15.75 µin]
Barrel Type	Open



Contact Type	Socket
Contact Mating Area Plating Material	Tin (Sn)
Wire Contact Termination Area Plating Material	Tin
Contact Retention Within Housing	With
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	9 A

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
Contact Retention Type Within Housing	Locking Lance

Dimensions

Compatible Insulation Diameter Range	.64 – 2.92 mm[.05 – .115 in]
Wire Size	236.823 – 1578.82 CMA

Usage Conditions

Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Packaging Features

Packaging Quantity	6500
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC



Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 58514-1
PROCrimp TL W/DIE MR26-18

TE Part # 5-2151229-1
OCEAN-2.0-APPLICATOR-S-055F120F-RSM

TE Part # 5-2151229-2
OCEAN-2.0-APPLICATOR-S-055F120F-RSA

TE Part # 2063388-1
TOOL, EXTRACTION

TE Part # 58514-2
PROCrimp DIE MR26-18

TE Part # 2151229-2
OCEAN-2.0-APPLICATOR-S-055F120F-RSA

TE Part # 2305570-1
Strip Terminal Cutter-Side Feed-No Crimp

TE Part # 7-2151229-7
OCEAN_2.0_SPARE_PART_KIT-055F120F


TE Part # 2151229-1
OCEAN-2.0-APPLICATOR-S-055F120F-RSM

TE Part # 91526-1
CCII MR II+ REC 26-18 ASSY

Also in the Series | AMP Miniature Rectangular MR



Connector Caps & Covers(15)




Connector Contacts(20)



Connector Hardware(2)



Connector Strain Relief(9)



PCB Headers & Receptacles(57)



Power Contacts(20)




Rectangular Power Connectors(77)




Wire-to-Board Headers & Receptacles (57)


Customers Also Bought



TE Part #1-640520-0
06P MR II PLUG HSG




TE Part #1-640518-0
03P MR II PLUG HSG




TE Part #640545-1
MR SPLIT PIN 26-18 PTPHBRZ LP




TE Part #SGH-80-4
STRING POT, 80 INCH RANGE




TE Part #1-480594-9
36P STR/REL HNGD



TE Part #1-640517-0
02P MR II PLUG HSG




TE Part #1-640510-0
06P MR II CAP HSG V0



TE Part #62056-2
250 FASTON FLAG REC 18-12 AWG SPBZ



TE Part #41472
RING TERMINAL 20-16 AWG TPBR



TE Part #350969-1
MR GRND PIN 26-18 PTPPHBZ

Documents



CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_641294-1_T.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_641294-1_T.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_641294-1_T.3d_stp.zip

English

Customer View Model

ENG_CVM_641294-1_E1.3d_igs.zip

English

Customer View Model

ENG_CVM_641294-1_E1.3d_stp.zip

English

Customer View Model

ENG_CVM_641294-1_E1.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

Product Specifications

Application Specification

English