



Connectors > Contacts > Connector Contacts



Contact Type: **Socket**  
Contact Mating Area Plating Material: **Tin-Lead**  
Wire Contact Termination Area Plating Material: **Tin-Lead**  
Contact Retention Within Housing: **With**  
Contact Size: **Size 16**

Features

Contact Features

|                                                       |                  |
|-------------------------------------------------------|------------------|
| Contact Underplating Material                         | Nickel           |
| Contact Orientation                                   | Straight         |
| Mating Pin Diameter                                   | 1.57 mm[.062 in] |
| Contact Underplating Material Thickness               | .76 µm[30 µin]   |
| Contact Mating Area Plating Material Thickness        | 2.54 µm[100 µin] |
| Wire Contact Termination Area Plating Material Finish | Matte            |
| Wire Contact Termination Area Plating Thickness       | 2.54 µm[100 µin] |
| Contact Type                                          | Socket           |
| Contact Mating Area Plating Material                  | Tin-Lead         |
| Wire Contact Termination Area Plating Material        | Tin-Lead         |
| Contact Retention Within Housing                      | With             |
| Contact Size                                          | Size 16          |
| Contact Base Material                                 | Brass            |
| Contact Current Rating (Max)                          | 13 A             |

Termination Features



|                                    |              |
|------------------------------------|--------------|
| Termination Method to Wire & Cable | Crimp        |
| Product Terminates To              | Wire & Cable |

Mechanical Attachment

|                         |      |
|-------------------------|------|
| Wire Insulation Support | With |
|-------------------------|------|

Dimensions

|                                      |                              |
|--------------------------------------|------------------------------|
| Compatible Insulation Diameter Range | 2.03 – 2.54 mm [.08 – .1 in] |
| Wire Size                            | .8 – 1.4 mm <sup>2</sup>     |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -55 – 90 °C [-67 – 194 °F] |
|-----------------------------|----------------------------|

Operation/Application

|                     |                |
|---------------------|----------------|
| Circuit Application | Power & Signal |
|---------------------|----------------|

Packaging Features

|                    |      |
|--------------------|------|
| Packaging Quantity | 4000 |
| Packaging Method   | Reel |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Not Compliant                                                                                                                                                                                                                                                                                                                                                                                                           |
| EU ELV Directive 2000/53/EC                   | Compliant with Exemptions                                                                                                                                                                                                                                                                                                                                                                                               |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold                                                                                                                                                                                                                                                                                                                                                                                    |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2025 (247)<br>Candidate List Declared Against: JAN 2025 (247)<br>SVHC > Threshold:<br>Pb (13% in 4690948374)<br><b>Article Safe Usage Statements:</b><br>Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                                                                                                                                                                                                                                                                                                                     |
| Solder Process Capability                     | Not applicable for solder process capability                                                                                                                                                                                                                                                                                                                                                                            |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

|                                                                                                                                                         |                                                                                                                                                         |                                                                                                                                                            |                                                                                                                                                              |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  <p>TE Part # 5-2151023-2<br/>OCEAN_2.0_Applicator-S-080F1200-RSA</p> |  <p>TE Part # 2151023-2<br/>OCEAN_2.0_Applicator-S-080F1200-RSA</p>  |  <p>TE Part # 305183<br/>EXTRACT TOOL TYPE 2 20-16</p>                 |  <p>TE Part # 2305570-1<br/>Strip Terminal Cutter-Side Feed-No Crimp</p> |
|  <p>TE Part # 58495-2<br/>PROCRIMPER DIE ASSY MULTIMATE</p>          |  <p>TE Part # 539972-1<br/>EXTRACTION TOOL</p>                      |  <p>TE Part # 2151023-1<br/>OCEAN_2.0_Applicator-S-080F1200-RSM</p>   |  <p>TE Part # 91505-1<br/>CCII TYPE III+ 24-16 ASSY</p>                 |
|  <p>TE Part # 58495-1<br/>PRO CRIMPER ASSY MULTIMATE</p>             |  <p>TE Part # 7-2151023-7<br/>OCEAN_2.0_SPARE_PART_KIT-080F1200</p> |  <p>TE Part # 5-2151023-1<br/>OCEAN_2.0_Applicator-S-080F1200-RSM</p> |  <p>TE Part # 200893-2<br/>INSERTION TOOL CONT</p>                      |

Also in the Series | AMP Type III+

|                                                                                                                    |                                                                                                                                 |                                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
|  <p>Connector Contacts(260)</p> |  <p>Insertion &amp; Extraction Tools(4)</p> |  <p>Power Contacts(260)</p> |
|--------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|



Also in the Series

Circular Plastic Connectors Series 1

Circular Power Connectors(211)

Connector Contacts(260)

Power Contacts(260)

Customers Also Bought

TE Part #1241637-1  
6pos MQS .63 header 90deg

TE Part #1-480711-0  
15P UMNL CAP HSG NATL

TE Part #929990-1  
1,5MM SOCK CONTACT

TE Part #207486-2  
RECEPT,SZ 23-16,CPC

TE Part #66259-4  
MALE CONTACT ASSY. (L.P.)

TE Part #3-770060-1  
MINI AMP-IN PTLP/PHBZ

TE Part #2266116-1  
OCEAN\_2.0\_Applicator-S-069F110O-RSM

TE Part #10200493-00  
LS503-31313 LIQUID LEVEL SENSO RSM

TE Part #1241415-1  
AMP MCP 6.3/4.8K, CONTACT, SWS, (LP)

TE Part #953382-3  
COVER FOR 6W HSG MQS GEN2

Documents

Product Drawings

III+ SKT,18-16,TIN-LEAD,STRIP

English

CAD Files

Customer View Model

ENG\_CVM\_CVM\_66100-7\_BJ.2d\_dxf.zip



English

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_66100-7\\_BJ.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_66100-7\\_BJ.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

Japanese

[Instruction Sheet \(U.S.\)](#)

English

Agency Approvals

[Agency Approval Document](#)

English