



Connectors > Contacts > Connector Contacts



Contact Type: **Pin**

Contact Mating Area Plating Material: **Tin (Sn)**

Wire Contact Termination Area Plating Material: **Tin**

Operating Voltage: **250 VDC**

Features

Product Type Features

Sealable	No
----------	----

Electrical Characteristics

Operating Voltage	250 VDC
-------------------	---------

Contact Features

Contact Orientation	Straight
Mating Pin Diameter	1.57 mm[.062 in]
Contact Mating Area Plating Material Thickness	.4 µm[16 µin]
Wire Contact Termination Area Plating Material Finish	Bright
Wire Contact Termination Area Plating Thickness	.4 – 3.5 µm[16 – 138 µin]
Barrel Type	Open
Contact Mating Area Plating Material Finish	Semi-Bright
Contact Type	Pin
Contact Mating Area Plating Material	Tin (Sn)
Wire Contact Termination Area Plating Material	Tin
Contact Retention Within Housing	With



Contact Size	Size 16
Contact Base Material	Brass
Contact Current Rating (Max)	1.8 A

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Compatible Insulation Diameter Range	1.27 – 2.79 mm[.05 – .11 in]
Wire Size	.3 – .9 mm²

Usage Conditions

Operating Temperature Range	-55 – 90 °C[-67 – 194 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Packaging Features

Packaging Quantity	1500
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 66592-1
TYPE VI SKT CONT,M-MATE,LP

TE Part # 2844982-1
CCII TYPE VI MLTIMATE PIN/SKT 22-18 ASSY

Also in the Series | AMP Type IV

Connector Contacts(47)

Power Contacts(47)

Customers Also Bought

TE Part #66589-1
TYPE VI PIN CONT,M-MATE,LP

TE Part #1-770876-0
09P MINI UMNL HDR ASSY SN

TE Part #66582-2
TYPE VI SKT CONT,MULTI-MATE

TE Part #5747299-8
15 RCPT SP/FMS INSRT



TE Part #66253-8
MALE CONTACT ASSY. (STRIP)

TE Part #1546350-2
R/A CABLE CLAMP KIT, SZ 23, CPC

TE Part #322459
SPLICE, SOLIS BUTT STRAP 16-14

TE Part #1-770743-1
10P MINI UMNL HDR ASSY VRT LF

TE Part #968075-3
MPQ2,8 Ag rec LL unseal. >1-2,5

TE Part #745255-2
SPRING LATCH 2/BAG

Documents

Product Drawings

TYPE VI PIN CONT,M-MATE,LP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_66591-1_J.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_66591-1_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_66591-1_J.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

Japanese

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

Japanese



Instruction Sheet (U.S.)

English