CII

TE Internal #: 7-1617808-5

Time Delay Relay, DC, 2 Form C DPDT-CO, 10 A Contact Rating,

Chassis Mount, Hermetically Sealed, 125 °C [257 °F]

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: Time Delay Relay

Current Type: DC

Contact Arrangement: 2 Form C DPDT-CO

Contact Current Rating: 10 A

Main Termination & Connection Type: Solder Hook Terminals

## **Features**

#### **Product Type Features**

Product Type Features				
Relay & Contactor Type	Time Delay Relay			
Configuration Features				
Contact Arrangement	2 Form C DPDT-CO			
Electrical Characteristics				
Input Voltage	28 VDC			
Contact Current Rating	10 A			
Body Features				
Enclosure Type	Hermetically Sealed			
Contact Features				
Contact Material	Silver Cadmium Oxide			

### **Termination Features**

Main Termination & Connection Type	Solder Hook Terminals
Coil Termination & Connection Type	Solder Hook Terminals

### Mechanical Attachment

Dimensions	
Product Mount Type	Chassis Mount
Product Mounting Feature Type	Mounting Brackets



Product Width	25.79 mm[1.01 in]			
Product Length	43.6 mm[1.72 in]			
Product Height	25.4 mm[1 in]			
Usage Conditions				
Operating Temperature Range	-55 – 125 °C			
Environmental Ambient Temperature (Max)	125 °C[257 °F]			
Operation/Application				
Type of Control	Fixed			
Indicator Type	No Indicator			
Delay Time	500 seconds			
Mode of Operation	Delay on Operate			
Repeatability (Max)	±10%			
Current Type	DC			

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not lead free process capable

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the



product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

# Compatible Parts



# Customers Also Bought





















## **Documents**

Product Drawings
TD228-5003S=TDFO 500 SEC M83726/28-5003S

English

Time Delay Relay, DC, 2 Form C DPDT-CO, 10 A Contact Rating, Chassis Mount, Hermetically Sealed, 125 °C [257 °F]



Datasheets & Catalog Pages
High\_Performance\_Relays\_Section5

English