3430A2F680RTDF <

CGS | CGS 3430

TE Internal #: 7-2176554-0 680 ohm, Surface Mount Power Resistor, Thick Film, 0508, 1 W, 1 %, ±100 ppm/°C, Solder, 2 Terminations, .55 mm [.022 in] Height, CGS 3430

View on TE.com >





Resistance Value: 680Ω

Resistor Type: Power Resistor

Element Type: Thick Film

Package Size Code: 0508

Power Rating: 1W

Features

TE connectivity

Product Type Features

Resistor Type	Power Resistor
Element Type	Thick Film
Package Size Code	0508
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Operating Voltage	200 V
Resistance Value	680 Ω
Power Rating	1 VV
Resistance Class	Up to 1kΩ
Passive Component Tolerance	1 %
Termination Features	
Surface Mount Resistor Termination Type	Solder
Number of Terminations	2

3430A2F680RTDF

680 ohm, Surface Mount Power Resistor, Thick Film, 0508, 1 W, 1 %, ±100 ppm/°C, Solder, 2 Terminations, .55 mm [.022 in] Height, CGS 3430



Dimensions

Product Height	.55 mm[.022 in]
Product Length	1.25 mm[.049 in]
Product Width	2 mm[.079 in]
Usage Conditions	
Operating Temperature Range	-55 – 155 °C
Temperature Coefficient	±100 ppm/°C
Packaging Features	
Packaging Method	Taped & Reeled
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE

Halogen Content

Solder Process Capability

2024 (241) Does not contain REACH SVHC

BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.

Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

3430A2F680RTDF

680 ohm, Surface Mount Power Resistor, Thick Film, 0508, 1 W, 1 %, ±100 ppm/°C, Solder, 2 Terminations, .55 mm [.022 in] Height, CGS 3430





Also in the Series | CGS 3430



Customers Also Bought



Documents

Product Drawings 3430 A2 1% 680R 100ppm 1k RL

English

CAD Files Customer View Model

ENG_CVM_CVM_7-2176554-0_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_7-2176554-0_BA.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_7-2176554-0_BA.2d_dxf.zip

English

3D PDF

C For support call+1 800 522 6752

3430A2F680RTDF

680 ohm, Surface Mount Power Resistor, Thick Film, 0508, 1 W, 1 %, ±100 ppm/°C, Solder, 2 Terminations, .55 mm [.022 in] Height, CGS 3430



3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Datasheet - CGS 3430 Series

English

Automotive Grade Wide Terminal Chip Resistor - Type 3430 Series

English