




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **254 – 404 CMA**

Mating Tab Width: **2.8 mm, 3.18 mm [.11 in, .125 in]**

Features

Product Type Features

Terminal Features	Wire Stop
Insertion Force	Normal

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Electrical Characteristics

Voltage Rating	600 V
----------------	-------

Body Features

Insulation Material	Nylon
---------------------	-------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm, 3.18 mm[.11 in][.125 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass



Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Closed

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	18.7 mm[.735 in]
Compatible Insulation Diameter Range	2.54 mm[.1 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	254 – 404 CMA

Usage Conditions

Insulation Option	Fully Insulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
UL Flammability Rating	UL 94V-2

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece/Carton

Other

Barrel Color	Purple
--------------	--------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)



Candidate List Declared Against: JAN 2025 (247)
Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 58628-2
PROCRMP DIESET 26-14 ULTRAFast

TE Part # 58628-1
PROCRIMP T&D 26-14 ULTRAFast

Also in the Series | Ultra-Fast 110

Quick Disconnects(14)

Customers Also Bought



TE Part #160917-3
FF 250 REC 1-2.5MM2 PB

TE Part #2-2213767-1
AV19 SPL 3A MOVE RING LED WHITE 12V

TE Part #4-2213766-7
AV19 DPM 3A POWER LED RED 24V

TE Part #5-2213767-5
AV19 DPM 3A MOVE RING LED GREEN 24V

TE Part #2-6609956-2
PE00XD000=C4936

TE Part #2443734-3
COMBO 2,CHARGE INLET KIT 120 SQMM, NO AC

TE Part #4-2213767-7
AV19 DPM 3A MOVE RING LED RED 24V

TE Part #5-103948-2
5X3 MTE SHRD PIN SR LATCH .100

TE Part #5-2213767-1
AV19 DPM 3A MOVE RING LED YELLOW 24V

TE Part #1902937-1
C/A, BATTERY, BLUNT CUT, 24 IN LONG

Documents

Product Drawings

ULTRAFast 110 ASSY REC 26-22 TPBR LP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_7-520366-2_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_7-520366-2_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_7-520366-2_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



Ultra-Fast and Ultra Fast Plus

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Platform Crimping Die Assembly 58052-3

English

Agency Approvals

Agency Approval Document

English