747299-8 • ACTIVE

AMPLIMITE | AMPLIMITE HD-20

TE Internal #: 747299-8 15 Position D-Shaped Connector, Receptacle, Board-to-Board, Board Mount, 2 Shell Size, 2.74 mm [.108 in] Centerline, AMPLIMITE HD-20

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Receptacle Assembly: Vertical, Shell Size 2, 2.74mm



Number of Positions: 15 Connector & Housing Type: Receptacle Connector System: Board-to-Board Connector Mounting Type: Board Mount Connector Shell Size: 2

All D-Sub Receptacle Assembly: Vertical, Shell Size 2, 2.74mm (26)

Features

Product Type Features

Shell Material Configuration

Connector & Housing Type

Front Metal Shell

Receptacle

Connector System	Board-to-Board
Connector Shell Size	2
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
PCB Mount Orientation	Vertical
Number of Rows	2
Number of Positions	15
Body Features	
Shield Plating Material	Tin
Shield Material	Steel
Shell Plating Material	Tin
Mating Retention Feature Material	Brass
Primary Product Color	Black
Connector Profile	Standard
Contact Features	

C For support call+1 800 522 6752

15 Position D-Shaped Connector, Receptacle, Board-to-Board, Board Mount, 2 Shell Size, 2.74 mm [.108 in] Centerline, AMPLIMITE HD-20



Contact Underplating Material	Nickel
	30 µin
Contact Shape & Form	Round
Contact Mating Area Plating Material	Gold (Au)
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin-Lead
Contact Current Rating (Max)	6 A
Contact Options	Installed
Termination Features	
Termination Post & Tail Diameter	.66 mm[.026 in]
Termination Method to PCB	Through Hole - Solder
Termination Post & Tail Length	3.18 mm[.125 in]
Mechanical Attachment	
Mating Retention Type	Threaded Insert, 4-40 UNC
PCB Mount Retention	With
Mounting Hole Diameter	3.05 mm[.12 in]
Mating Retention	With
PCB Mount Retention Type	Mounting Hole
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Polyester
Shell Material	Carbon Steel
Centerline (Pitch)	2.74 mm[.108 in]
Dimensions	
Row-to-Row Spacing	2.84 mm[.112 in]
PCB Thickness (Recommended)	1.57 – 2.36 mm[.062 – .093 in]
Jsage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Shielded	Yes
Circuit Application	Signal

C For support call+1 800 522 6752

15 Position D-Shaped Connector, Receptacle, Board-to-Board, Board Mount, 2 Shell Size, 2.74 mm [.108 in] Centerline, AMPLIMITE HD-20



UL Flammability Rating	UL 94V-0
Compatible With Approved Standards Products	UL E28476
Packaging Features	
Packaging Quantity	13
Packaging Method	Tube
Product Compliance For compliance documentation, visit the product page on TE.com>	Not Compliant
EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (13% in 4690948374) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900

ppm.

Solder Process Capability

Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

15 Position D-Shaped Connector, Receptacle, Board-to-Board, Board Mount, 2 Shell Size, 2.74 mm [.108 in] Centerline, AMPLIMITE HD-20





Also in the Series | AMPLIMITE HD-20



Customers Also Bought













TE Part #2-5174339-5 AMPLIMITE CAP HEADER

TE Part #1586518-2 08P CMNL HDR ASSY PC NATL LF TE Part #1586520-2 12P CMNL HDR ASSY PC NATL LF TE Part #1625854-1 1206 PROBE PAD



15 Position D-Shaped Connector, Receptacle, Board-to-Board, Board Mount, 2 Shell Size, 2.74 mm [.108 in] Centerline, AMPLIMITE HD-20



Documents

Product Drawings 15 RCPT SP/FMS INSRT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_747299-8_R.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_747299-8_R.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_747299-8_R.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English