AMP | AMPSEAL

TE Internal #: 770680-1

23 Position Housing, Plug, Wire-to-Board, 4 mm [.157 in]

Centerline, Sealable, Black, Wire & Cable, Power, Cable Mount

(Free-Hanging), AMPSEAL

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > AMPSEAL Receptacle Housings











Number of Positions: 23

Connector & Housing Type: Plug

Mating Pin Diameter: 1.3 mm [.051 in]

Connector System: Wire-to-Board

Centerline (Pitch): 4 mm [.157 in]

All AMPSEAL Receptacle Housings (31)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	Yes
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	23
Number of Rows	3
Electrical Characteristics	

250 VAC

Operating Voltage



Nominal Voltage Architecture	250 V
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	A
Contact Features	
Contact Size	1.3mm
Contact Type	Socket
Mating Pin Diameter	1.3 mm[.051 in]
Contact Current Rating (Max)	17 A
Mechanical Attachment	
Strain Relief	Add By Accessory
Terminal Position Assurance	Yes
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT
Centerline (Pitch)	4 mm[.157 in]
Dimensions	
Row-to-Row Spacing	4 mm[.157 in]
Product Width	33.6 mm[1.323 in]
Product Length	47.4 mm[1.866 in]
Connector Height	34.6 mm[1.362 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
IP Rating	IP67, IP69K
UL Flammability Rating	UL 94V-0



Packaging Features

Packaging Quantity	28	
Packaging Method	Tray	
Other		
Connector Position Assurance Capable	No	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Dodecamethylcyclohexasiloxane (D6) (.5% in 27520126669) Decamethylcyclopentasiloxane (D5) (.5% in 27520126669) Octamethylcyclotetrasiloxane (D4) (.5% in 27520056317) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-J04-ARH AMPSEAL Robust Headers



TE Part # 2437604-1 AMPSEAL HDR 23P VERTICAL COD1,



TE Part # 2373965-1 CPA,AMPSEAL



PRO-CRIMPER III TOOL AMPSEAL















Also in the Series | AMPSEAL




Automotive Connector Locks & Position Assurance(1)



Automotive Terminals(8)





Customers Also Bought





STRAIN RELIEF,23 POSITION

AMPSEAL













Documents

Product Drawings

23POS, AMPSEAL, SOC HSG ASSY, SLD, COD 1

English

CAD Files

Customer View Model

ENG_CVM_CVM_770680-1_L.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_770680-1_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_770680-1_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

AMPSEAL Connector Series

English

AMPSEAL Connector Catalog

English

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Engineering Report

English

Instruction Sheets

Instruction Sheet (U.S.)

English

23 Position Housing, Plug, Wire-to-Board, 4 mm [.157 in] Centerline, Sealable, Black, Wire & Cable, Power, Cable Mount (Free-Hanging), AMPSEAL



Agency Approvals

UL Report

English