




Connectors > Contacts > Connector Contacts



Contact Type: **Receptacle**

Contact Mating Area Plating Material: **Tin (Sn)**

Wire Contact Termination Area Plating Material: **Tin**

Operating Voltage: **250 VDC**

Features

Product Type Features

Discrete Wire Type	Stranded
Sealable	No

Electrical Characteristics

Operating Voltage	250 VDC
-------------------	---------

Contact Features

Contact Orientation	Straight
Contact Mating Area Plating Material Thickness	1.5 – 4 µm[59.05 – 157.48 µin]
Mating Square Post Dimension	.64 mm[.025 in]
Wire Contact Termination Area Plating Material Finish	Bright
Wire Contact Termination Area Plating Thickness	1.5 – 4 µm[59.05 – 157.5 µin]
Barrel Type	Open
Contact Mating Area Plating Material Finish	Bright
Contact Type	Receptacle
Contact Mating Area Plating Material	Tin (Sn)
Wire Contact Termination Area Plating Material	Tin



Contact Retention Within Housing	With
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	5 A

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
Contact Retention Type Within Housing	Locking Lance

Dimensions

Compatible Insulation Diameter Range	.89 – 1.52 mm[.035 – .06 in]
Wire Size	404 – 1022 CMA

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	VDE
---	-----

Packaging Features

Packaging Quantity	15000
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per



homogenous material. Also BFR/CFR/PVC Free



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

			
TE Part # CAT-AQ6-HPCI High-Power Charging CCS1 and CCS2 Inlet Kits	TE Part # 7-2837550-7 OCEAN_2.0_SPARE_PART_KIT-050F070F	TE Part # 2151022-2 OCEAN_2.0_APPLICATOR-S-055F070F-RSA	TE Part # 2837550-2 OCEAN_2.0_Applicator-S-050F070F-RSA
			
TE Part # 2443741-2 COMBO 2,CHARGE INLET KIT 95SQMM, W/O LED	TE Part # 7-2151022-7 OCEAN_2.0_SPARE_PART_KIT-055F070F	TE Part # 91391-2 SDE COMM MICRO MNL DIE SET	TE Part # 2481865-1 CHARGE INLET ASSY,EK0 CCST1
			
TE Part # 2837550-1 OCEAN_2.0_Applicator-S-050F070F-RSM	TE Part # 843996-6 TOOL, EXTRACTION RESET	TE Part # 91391-1 SDE PEW 12MICRO MNL HAND TOOL	TE Part # 91501-1 CCII MICRO MNL REC 24-20 ASSY



TE Part # 2151022-1
OCEAN_2.0_APPLICATOR-S-055F070F-RSM



TE Part # 2425486-1
MICRO MNL BLIND MATE HINGED TPA PLUG 6P


Also in the Series | Micro MATE-N-LOK



Connector Contacts(27)



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(371)




Power Contacts(27)



Rectangular Connector Housings(98)



Rectangular Power Connectors(469)



Wire-to-Board Headers & Receptacles (371)

Customers Also Bought



TE Part #2-1879353-1
RR02 5% 30K AMMO



TE Part #1445022-8
MICRO MNL RFECPT HSG SINGLE R



TE Part #1445022-3
MICRO MNL RFECPT HSG SINGLE R



TE Part #1-794617-0
10POS,MICRO MNL,RCPT HSG



TE Part #794617-8
8POS,MICRO MNL,RCPT HSG




TE Part #1-794617-2
12POS,MICRO MNL,RCPT HSG



TE Part #CQ50423001
RAY-101-4.0(10)



TE Part #6651585-2
CONN,PIN,CUSTOM CONN



Documents

CAD Files

Customer View Model

ENG_CVM_CVM_794606-1_K.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_794606-1_K.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_794606-1_K.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

MICRO MATE-N-LOK CONNECTOR SYSTEM

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English