TE Internal #: 8-1393127-9

General Purpose Power Relay, DC, Monostable, 1 Form X SPST-NO-DM, 20 A Contact Rating, 24 VDC Coil Voltage, 600 VAC Contact

Voltage

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: General Purpose Power Relay

Current Type: DC

Coil Magnetic System: Monostable

Contact Arrangement: 1 Form X SPST-NO-DM

Contact Current Rating: 20 A

Features

Product Type Features

Relay & Contactor Type	General Purpose Power Relay
Configuration Features	
Contact Number of Poles	2
Contact Arrangement	1 Form X SPST-NO-DM
Electrical Characteristics	
Coil Resistance	288 Ω
Contact Switching Voltage (Max)	600 VAC
Contact Current Rating	20 A
Coil Voltage Rating	24 VDC
Contact Voltage Rating	125 VDC
Coil Power Rating DC	2 W
Insulation Initial Dielectric Between Contacts & Coil	2000 Vrms
Termination Features	
Main Termination & Connection Type	8-32 Screw
Coil Termination & Connection Type	6-32 Screw
Mechanical Attachment	

Panel Mount

Product Mount Type



Product Width	63.8 mm
Product Length	63.3 mm
Product Height	63.5 mm
Usage Conditions	
Operating Temperature Range	-55 – 80 °C[-67 – 176 °F]
Environmental Ambient Temperature (Max)	80 °C[176 °F]
Operation/Application	
Current Type	DC
Coil Magnetic System	Monostable

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Cd (7.5% in Component Part) Cadmium oxide (9.9% in M-3125-3) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts



Customers Also Bought



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_8-1393127-9_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-1393127-9_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_8-1393127-9_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

PRD 10 to 50 Amp Heavy Duty AC or DC Power Relay

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

UL

General Purpose Power Relay, DC, Monostable, 1 Form X SPST-NO-DM, 20 A Contact Rating, 24 VDC Coil Voltage, 600 VAC Contact Voltage



English