



CII

TE Internal #: 8-1617808-0

Time Delay Relay, DC, 2 Form C DPDT-CO, 10 A Contact Rating,  
Panel & Socket Mount, Hermetically Sealed, 125 °C [257 °F]

[View on TE.com >](#)

Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: **Time Delay Relay**

Current Type: **DC**

Contact Arrangement: **2 Form C DPDT-CO**

Contact Current Rating: **10 A**

Main Termination & Connection Type: **Socket Pins**

Features

Product Type Features

|                        |                  |
|------------------------|------------------|
| Relay & Contactor Type | Time Delay Relay |
|------------------------|------------------|

Configuration Features

|                     |                  |
|---------------------|------------------|
| Contact Arrangement | 2 Form C DPDT-CO |
|---------------------|------------------|

Electrical Characteristics

|                        |        |
|------------------------|--------|
| Input Voltage          | 28 VDC |
| Contact Current Rating | 10 A   |

Body Features

|                |                     |
|----------------|---------------------|
| Enclosure Type | Hermetically Sealed |
|----------------|---------------------|

Contact Features

|                  |                      |
|------------------|----------------------|
| Contact Material | Silver Cadmium Oxide |
|------------------|----------------------|

Termination Features

|                                    |             |
|------------------------------------|-------------|
| Main Termination & Connection Type | Socket Pins |
| Coil Termination & Connection Type | Socket Pins |

Mechanical Attachment

|                               |                      |
|-------------------------------|----------------------|
| Product Mounting Feature Type | Mounting Brackets    |
| Product Mount Type            | Panel & Socket Mount |

Dimensions

|  |  |
|--|--|
|  |  |
|--|--|



|                |                  |
|----------------|------------------|
| Product Width  | 25.6 mm[1 in]    |
| Product Length | 43.6 mm[1.72 in] |
| Product Height | 25.4 mm[1 in]    |

Usage Conditions

|   |                |
|---|----------------|
| Operating Temperature Range             | -55 – 125 °C   |
| Environmental Ambient Temperature (Max) | 125 °C[257 °F] |

Operation/Application

|                     |                  |
|---------------------|------------------|
| Type of Control     | Fixed            |
| Indicator Type      | No Indicator     |
| Delay Time          | 90 seconds       |
| Mode of Operation   | Delay on Release |
| Repeatability (Max) | ±10%             |
| Current Type        | DC               |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|   |   |
|---|---|
| EU RoHS Directive 2011/65/EU                  | Not Compliant   |
| EU ELV Directive 2000/53/EC                   | Not Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold  |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2025 (247)<br>Candidate List Declared Against: JAN 2024 (240)<br>Does not contain REACH SVHC |
| Halogen Content                               | Not Yet Reviewed for halogen content  |
| Solder Process Capability                     | Not lead free process capable   |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the



product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



TE Part # 2-1617749-5  
[FCA-210-1027M=M83536/10-027M](#)

Customers Also Bought



TE Part #ABC06N-22S  
[IN-LINE PLUG](#)



TE Part #843037-000  
[101A062-3-0](#)



TE Part #843056-000  
[101A073-3-0](#)




TE Part #046377-000  
[222A132-25/225-0](#)



TE Part #3-1437559-7  
[MTL206N=\(MSTL\) SW TOG LOCKING](#)



TE Part #CM6243-000  
[HEX40-KC-00-11-A2-1](#)



TE Part #814710-000  
[202A132-3/42-0](#)



TE Part #913833-000  
[D-100-00-RS](#)



TE Part #826415-000  
[TTMS-12.7-9](#)



TE Part #992021-000  
[RTD-50-M-00-H](#)

Documents

- CAD Files
- 3D PDF
- 3D



Customer View Model

[ENG\\_CVM\\_CVM\\_8-1617808-0\\_A.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_8-1617808-0\\_A.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_8-1617808-0\\_A.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[High\\_Performance\\_Relays\\_Section5](#)

English