# 8-323994-2 ACTIVE

#### PIDG

TE Internal #: 8-323994-2

Butt Splice, 26 – 22 AWG, .12 – .4 mm<sup>2</sup> Wire, Serrated, .202 – .81

kcmil, 202 – 810 CMA, Copper, Yellow - Translucent, 8 Serration,

PIDG

View on TE.com >



Terminals & Splices > Splices > PIDG Butt Splices











Splice Type: Butt Splice
Wire Size: .12 – .4 mm²

Sealable: No

Splice Features: Serrated

All PIDG Butt Splices (25)

### Features

#### **Product Type Features**

Splice Accessory Type	Splice
Splice Type	Butt Splice
Sealable	No
Compatible With Discrete Wire Type	Stranded
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Serrations	8
Compatible With Wire & Cable Type	Discrete Wire
Body Features	

.411 g

Serrated

Copper, Nylon

Yellow - Translucent

Product Weight

Splice Features

Insulation Material

Primary Product Color



#### **Contact Features**

Terminal Plating Material	Tin
Contact Base Material	Copper
Barrel Type	Closed
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	.202 – .81 kcmil
Compatible Insulation Diameter Range	2.08 mm[.082 in]
Terminal Material Thickness	.38 mm[.015 in]
Product Length	22.61 mm[.89 in]
Usage Conditions	
Insulation Option	Fully Insulated
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	50
Packaging Method	Loose Piece

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer




This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### Compatible Parts







### Also in the Series | PIDG



Compression Connectors(17)



Crimp Wire Pins, Tabs & Ferrules(41)




Hand Crimping Tools(2)




Knife Disconnects(11)



Ring Terminals(588)



Spade Terminals(228)



Special Purpose Terminals(1)



Splices(41)

## **Customers Also Bought**






TE Part #4-1393247-2 W31-X2M1G-5=W23/W31



TE Part #8-33462-1 TERM, SOLIS, R, 8, M8(5/16)



PIDG 26-22 BUTT SM-PACK-25






TE Part #1-535541-2 14 MODIV VRT SR CE 100/115













#### **Documents**

**Product Drawings** SPLICE BUTT PIDG 26-22

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_8-323994-2\_Y.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_8-323994-2\_Y.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_8-323994-2\_Y.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Butt Splice, 26-22 AWG, .12-.4 mm $^2$  Wire, Serrated, .202-.81 kcmil, 202-810 CMA, Copper, Yellow - Translucent, 8 Serration, PIDG



PIDG Terminals and Splices Quick Reference Guide

English