8-323994-3 ACTIVE

PIDG

TE Internal #: 8-323994-3

Butt Splice, 26 – 22 AWG, .12 – .4 mm² Wire, Serrated, .202 – .81 kcmil, 202 – 810 CMA, Copper, Yellow - Translucent, 8 Serration,

PIDG

View on TE.com >



Terminals & Splices > Splices > PIDG Butt Splices











Splice Type: Butt Splice Wire Size: .12 – .4 mm²

Sealable: No

Splice Features: Serrated

All PIDG Butt Splices (25)

Features

Product Type Features

Product Weight

Splice Features

Insulation Material

Primary Product Color

Splice Accessory Type	Splice
Splice Type	Butt Splice
Sealable	No
Compatible With Discrete Wire Type	Stranded
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Serrations	8
Compatible With Wire & Cable Type	Discrete Wire
Body Features	

4.536 g

Serrated

Copper, Nylon

Yellow - Translucent



Contact Features

Terminal Plating Material	Tin
Contact Base Material	Copper
Barrel Type	Closed
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	.202 – .81 kcmil
Compatible Insulation Diameter Range	2.08 mm[.082 in]
Terminal Material Thickness	.38 mm[.015 in]
Product Length	22.61 mm[.89 in]
Usage Conditions	
Insulation Option	Fully Insulated
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	25
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Also in the Series | PIDG



Compression Connectors(17)



Crimp Wire Pins, Tabs & Ferrules(41)




Knife Disconnects(11)



Quick Disconnects(38)



Ring Terminals(588)



Spade Terminals(228)



Special Purpose Terminals(1)



Splices(41)

Customers Also Bought





















Documents

Product Drawings

PIDG 26-22 BUTT SM-PACK-25

English

ORA

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_8-323994-3_Y.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-323994-3_Y.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_8-323994-3_Y.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Butt Splice, 26-22 AWG, .12-.4 mm 2 Wire, Serrated, .202-.81 kcmil, 202-810 CMA, Copper, Yellow - Translucent, 8 Serration, PIDG



PIDG Terminals and Splices Quick Reference Guide

English