



Terminals & Splices > Splices



Splice Type: **Butt Splice**
Wire Size: **8 mm²**
Sealable: **No**
Splice Features: **Sight Hole**

Features

Product Type Features

Splice Accessory Type	Splice
Splice Type	Butt Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Body Features

Product Weight	4.622 g
Splice Features	Sight Hole

Contact Features

	100 μin
Terminal Plating Material	Tin
Contact Base Material	Copper



Barrel Type	Closed
-------------	--------

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions

Outside Diameter	7.52 mm[.296 in]
Wire Size	13100 – 20800 CMA
Barrel Inside Diameter	4.37 mm[.172 in]
Terminal Material Thickness	1.3 mm[.051 in]
Product Length	21.01 mm[.827 in]

Usage Conditions

Insulation Option	Uninsulated
-------------------	-------------

Operation/Application

Compatible With Wire Base Material	Copper
------------------------------------	--------

Industry Standards

Government Qualified Splice	No
-----------------------------	----

Packaging Features

Packaging Quantity	20
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 69355
HHHT SOLIS SOLIS FLAG STRATO 8 ASSY

Customers Also Bought

TE Part #1-1462039-8
IM06DGR=IM RELAY 140mW 12V

TE Part #2301826-2
AMPL PLUG HD20, VERT, 9P, B/L,4-40 S/LOC

TE Part #650110-000
D-436-0128

TE Part #34318
SPLICE, SOLIS, PARA, 8

TE Part #ADP-NF-NF-B-W
N Type Jack to N Type Jack Bulkhead

TE Part #K1060041
Relay 30-311-12

TE Part #CSD-SMAM-610-NM
SMA to SMA 610mm RG58

TE Part #331401
SOLISTRAND RING 26-22 #6



Documents

Product Drawings

[SPLICE,SOLIS BUTT 8](#)

English

CAD Files

[3D PDF](#)

English

Customer View Model

[ENG_CVM_8-36906-3_E.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_8-36906-3_E.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_8-36906-3_E.2d_dxf.zip](#)

English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_8-36906-3_H.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_8-36906-3_H.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_8-36906-3_H.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOLISTRAND - QRG](#)

English

Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

English

8-36906-3

Butt Splice, 8 AWG, 8 mm² Wire, Sight Hole, 13100 – 20800 CMA, Copper, 21.01 mm [.827 in] Length, Loose Piece, Closed Barrel, Solid / Stranded Wire

