




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **238 – 475 CMA**

Mating Tab Width: **4.75 mm [.187 in]**

Features

Product Type Features

Terminal Features	Wire Stop
Insertion Force	Normal

Electrical Characteristics

Voltage Rating	300 V
----------------	-------

Body Features

Insulation Material	Nylon
---------------------	-------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	Compression Crimp
Barrel Type	Closed



Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	17.81 mm[.7 in]
Compatible Insulation Diameter Range	2.08 mm[.082 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	238 – 475 CMA

Usage Conditions

Insulation Option	Partially Insulated
-------------------	---------------------

Packaging Features

Packaging Quantity	100
Packaging Method	Loose Piece

Other

Barrel Color	Yellow
--------------	--------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



REPRESENTATION ONLY

TE Part # 169485
DAHT PIDG PG 26-22 ASSY



REPRESENTATION ONLY

TE Part # 48518-2
DAHT PIDG FASTON 26-24 ASSY

Also in the Series | FASTON 187



Crimp Terminal Housings(40)



Insertion & Extraction Tools(1)



Insulation Boots & Sleeves(1)



Joints & Splices(1)



PCB Terminals(42)




Quick Disconnects(205)



Splices(1)

Customers Also Bought





TE Part #2-917780-1
[2.5 S.D.L POST HDR ASY 2P STD](#)



TE Part #CAT-P592-R472A
[PIDG Ring Tongue Terminals](#)



TE Part #2383942-4
[TERMI-BLOK SMD MOUNT 180_4P_3.5 MM](#)



TE Part #52942
[TERMINAL,PIDG SPR SPD 12-10 8](#)




TE Part #2383942-6
[TERMI-BLOK SMD MOUNT 180_6P_3.5 MM](#)



TE Part #350550-1
[UMNL SOK 20-14 PTPBR L/P](#)



TE Part #5212044-1
[5 CIRC DIN RCPT GRND SHLD](#)



TE Part #641321-1
[RECEPT PIDG FASTON 26-24 187](#)

Documents

Product Drawings

[RECEPT PIDG FASTON 26-24 187](#)

English

CAD Files

[3D PDF](#)

English

Customer View Model

[ENG_CVM_8-641321-1_H.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_8-641321-1_H.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_8-641321-1_H.2d_dxf.zip](#)

English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_8-641321-1_F.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_8-641321-1_F.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_8-641321-1_F.3d_stp.zip](#)

English



By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals

CSA Certificate

English