

MEAS | MEAS 86 TE Internal #: 86-500A-R TE Internal Description: 500 PSIA RIBBON CABLE MV PRESSURE SENSOR View on TE.com >



Sensors > Pressure Sensors > Media Isolated Pressure Sensors



Pressure Sensor Type: mV Output Pressure Sensors

Pressure Type: Absolute

Output Signal Type: 100mV

Operating Temperature Range: -40 – 125 °C [-40 – 257 °F]

Sensor Package: O-Ring Mount

Features

Product Type Features

Pressure Sensor Type

Pressure Type

Sensor Package

mV Output Pressure Sensors

Absolute

O-Ring Mount

Configuration Features

Electrical Connection	Ribbon Cable
Electrical Characteristics	
Supply Current	1.5 mA
Dimensions	
Product Diameter	15.82 mm[.622 in]
Product Height	11.4 mm[.448 in]
Usage Conditions	
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	
Proof Pressure Range	3X
Output Signal Type	100mV
Other	
Non-Linearity ±	.1 %

500 PSIA RIBBON CABLE MV PRESSURE SENSOR



Sensor (Options
----------	---------

No Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Tetraglyme (2% in Component Part) Methanone, (diphenylphosphinyl)(2,4,6- trimethylphenyl)- (1% in Component Part) Aticle Safe Usage Statements Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




500 PSIA RIBBON CABLE MV PRESSURE SENSOR






Also in the Series | MEAS 86



Customers Also Bought









86-500A-R

500 PSIA RIBBON CABLE MV PRESSURE SENSOR



Documents

CAD Files 3D PDF

3D

Customer View Model

ENG_CVM_CVM_86-500A-R_G1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_86-500A-R_G1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_86-500A-R_G1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 86C

English