




Connectors > Contacts > Connector Contacts



Contact Type: **Socket**
Contact Mating Area Plating Material: **Gold (Au)**
Wire Contact Termination Area Plating Material: **Gold Flash**
Operating Voltage: **250 VAC**
Contact Retention Within Housing: **With**

Features

Product Type Features

Discrete Wire Type	Stranded
Applied Pressure	Standard
Sealable	No

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Electrical Characteristics

Termination Resistance	12 mΩ
Insulation Resistance	5000 MΩ
Dielectric Withstanding Voltage (Max)	750 V
Operating Voltage	250 VAC

Contact Features

Contact Underplating Material	Nickel
Contact Orientation	Straight
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]



Mating Square Post Dimension	.64 mm[.025 in]
Contact Length	11.3 mm[.445 in]
Barrel Type	Open
Contact Type	Socket
Contact Mating Area Plating Material	Gold (Au)
Wire Contact Termination Area Plating Material	Gold Flash
Contact Retention Within Housing	With
Contact Size	.64mm
Contact Base Material	Beryllium Copper
Contact Current Rating (Max)	3 A

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
Contact Retention Type Within Housing	Locking Lance

Dimensions

Compatible Insulation Diameter Range	1.55 mm[.061 in]
Wire Size	236.823 – 789.41 CMA

Usage Conditions

Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards


Compatible With Approved Standards Products	CSA LR7189, UL E28476
---	-----------------------

Packaging Features

Packaging Quantity	12500
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>





EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 6-87631-4
58 MODIV HSG DR MRKD .100 POL

TE Part # 1-87977-6
36 MODIV HSG DR MRKD .100 POL

TE Part # 1-87977-4
32 MODIV HSG DR MRKD .100POL

TE Part # 5-87977-7
56 MODIV HSG DR MRKD .100 POL

TE Part # 3-87631-8
42 MODIV HSG DR MRKD .100 POL

TE Part # 6-87631-6
64 MODIV HSG DR MRKD .100 POL

TE Part # 87977-7
18 MODIV HSG DR MRKD .100 POL

TE Part # 5-87977-4
72 MODIV HSG COMP DR .100 POL







TE Part # 6-87631-3
58 MODIV HSG COMP DR .100 POL





TE Part # 4-87977-7
44 MODIV HSG COMP DR .100 POL





TE Part # 4-87631-3
52 MODIV HSG COMP DR .100 POL





TE Part # 1-102241-9
21 MODIV HSG COMP SR .100 POL





TE Part # 1-102241-7
19 MODIV HSG COMP SR .100 POL





TE Part # 5-87977-1
60 MODIV HSG COMP DR .100 POL





TE Part # 1-87456-9
24 MODIV HSG COMP DR .100CL





TE Part # 5-87456-9
48 MODIV HSG COMP DR .100CL





TE Part # 2151307-1
OCEAN_2.0_APPLICATOR-S-042F062O-RSM





TE Part # 4-87977-0
30 MODIV HSG COMP DR .100 POL






TE Part # 2-87977-4
60 MODIV HSG DR MRKD .100 POL





TE Part # 87922-1
10 MODIV HSG W/STR RLF DR MRKD

Also in the Series | AMPMODU IV/V




Backplane Connector Housings(1)



Connector Caps & Covers(11)




Connector Contacts(270)



Connector Hardware(10)



Insertion & Extraction Tools(4)



PCB Headers & Receptacles(517)



Power Contacts(206)

Customers Also Bought



TE Part #1-1375820-2
CST-100 II HOUSING 12 POS



TE Part #1-826942-6
16P MOD2 STIFT LEI



TE Part #5749205-1
80 50SR KIT,75D,UK



TE Part #87456-7
12 MODIV HSG COMP DR .100CL



TE Part #1-103168-8
40 MODII HDR DRST SHRD .100CL



TE Part #2-87631-4
28 MODIV HSG DR MRKD .100 POL




TE Part #58641-1
PRO-CRIMP TL & DIE MOD IV



TE Part #58517-3
PRO-CRIMPER II TOOL W/DIE SET



TE Part #4-641215-2
12P MTA100 HDR ASSY FL/ST 30AU



TE Part #2176732-6
HSC150S R27 5% Screw Terminal

Documents

Product Drawings

MOD IV RECP PLTD 30 SEL

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_87666-2_AH.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_87666-2_AH.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_87666-2_AH.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



AMP MODU IV & V Section of Catalog 1307819

English

AMPMODU_INTERCONNECTION_SYSTEM_SECTION5_CONT

English

Product Specifications

Application Specification

English