880584-1 ~ ACTIVE

AMP

TE Internal #: 880584-1 Novo Shunt, Closed Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -40 – 85 °C [-40 – 185 °F]

View on TE.com >



Connectors > PCB Connectors > Board-to-Board Connectors > Board-to-Board Jumpers & Shunts



Shunt Type: Novo Shunt Style: Closed Top Number of Positions: 2 Centerline (Pitch): 2.54 mm [.1 in] Contact Current Rating (Max): 3 A

Features

Product Type Features

Connector & Contact Terminates To

Connector System

Configuration Features

Number of Positions

Printed Circuit Board

Board-to-Board

2

Electrical Characteristics

| Termination Resistance | 15 mΩ | |
|--|-----------------|--|
| Insulation Resistance | 5000 MΩ | |
| Body Features | | |
| Primary Product Color | Black | |
| Handle | With | |
| Contact Features | | |
| Contact Mating Area Plating Material | Gold (Au) | |
| Contact Base Material | Phosphor Bronze | |
| Contact Mating Area Plating Material Thickness | .381 μm[15 μin] | |
| Shunt Type | Novo | |
| Shunt Style | Closed Top | |
| Contact Current Rating (Max) | 3 A | |
| Mechanical Attachment | | |
| | | |

C For support call+1 800 522 6752

880584-1

Novo Shunt, Closed Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -40 – 85 °C [-40 – 185 °F]



| Board Mount | |
|---------------------------|--|
| | |
| Thermoplastic | |
| 2.54 mm[.1 in] | |
| | |
| 14 mm[.551 in] | |
| | |
| -40 – 85 °C[-40 – 185 °F] | |
| | |
| Signal | |
| | |
| UL 94V-0 | |
| | |
| Loose Piece | |
| Loose Piece | |
| 1000 | |
| | |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant | |
|---|---|--|
| EU ELV Directive 2000/53/EC | Compliant | |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold | |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC | |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free | |
| Solder Process Capability | Not applicable for solder process capability | |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent

880584-1

Novo Shunt, Closed Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -40 – 85 °C [-40 – 185 °F]



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Customers Also Bought



TE Part #2-2324245-4 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5

TE Part #225251-E M12 MALE, A CODE, RA, 5P THR REAR MOUNT TE Part #3-794630-2 02P MICRO MNL ASSY,VRT,HDR,LF TE Part #1586040-4 4P VAL-U-LOK VRT HDR W/P V0

| TE Part #6339191-4 MJ,RJ45,SMT,SHLD,LED (G/Y) | TE Part #CAT-C339-SM1 SMD Power Resistor: 7 Watt, 200-2M Ohm | TE Part #5-103904-7 08 MTE HDR SRRA LATCH W/HLDWN | TE Part #5-103904-4 5 MTE HDR SRRA LATCH W/HLDWN |
|--|--|--|---|



TE Part #1759503-1 mini PCI-E 8H Type I PKG G/F

Documents

C For support call+1 800 522 6752

04/14/2025 09:19PM | Page 3

880584-1

Novo Shunt, Closed Top, 2 Position, 2.54 mm [.1 in] Centerline, Signal, -40 – 85 °C [-40 – 185 °F]



Product Drawings SHUNT CONNECTOR

English

CAD Files Customer View Model ENG_CVM_880584-1_L.3d_igs.zip

English

Customer View Model ENG_CVM_880584-1_L.3d_stp.zip

English

Customer View Model

ENG_CVM_880584-1_L.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Agency Approvals Agency Approval Document English