9-1393303-7 ACTIVE

Power Relay F

TE Internal #: 9-1393303-7

General Purpose Power Relay, DC, Monostable, 1 Form A (NO), 50

A Contact Rating, 24 VDC Coil Voltage, 24 VDC Contact Voltage,

Power Relay F

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: General Purpose Power Relay

Current Type: DC

Coil Magnetic System: Monostable

Contact Arrangement: 1 Form A (NO)

Contact Current Rating: 50 A

Features

Product Type Features

Relay & Contactor Type	General Purpose Power Relay
Configuration Features	
Contact Arrangement	1 Form A (NO)
Electrical Characteristics	
Contact Switching Load (Min)	1000mA @ 5VDC
Contact Limiting Short-Time Current	300 A
Contact Limiting Making Current	240 A
Coil Resistance	324 Ω
Contact Limiting Continuous Current	70 A
Contact Limiting Breaking Current	25 A
Insulation Initial Dielectric Between Open Contacts	500 Vrms
Contact Current Rating	50 A
Coil Voltage Rating	24 VDC
Contact Voltage Rating	24 VDC
Coil Power Rating DC	1.8 W
Insulation Initial Dielectric Between Contacts & Coil	500 Vrms
Body Features	

38 g[1.3 oz]

Product Weight



Enclosure Type	Dust Protected
Contact Features	
Contact Material	Silver Alloy
Termination Features	
Main Termination & Connection Type	Quick Connect Terminals
Coil Termination & Connection Type	Quick Connect Terminals
Mechanical Attachment	
Product Mount Type	Socket Mount
Dimensions	
Product Width	25.9 mm[1.019 in]
Product Length	25.9 mm[1.019 in]
Product Height	24.9 mm[.98 in]
Usage Conditions	
Environmental Category of Protection	RTI
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Current Type	DC
Coil Magnetic System	Monostable
Industry Standards	
IP Rating	IP54
Other	
Contact Current Class	>50 A
Coil Power Rating Class	1.5 W
Environmental Ambient Temperature Class	105 – 125 °C
Height Class (Mechanical)	20 – 25 mm
Length Class (Mechanical)	25 – 30 mm
	25 – 30 mm

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Power Relay F









Customers Also Bought



















TE Part #1-2819130-9
ABS CABLE ASSEMBLY 2110

TE Part #1-2375798-1 SNSR,AHG 323X220-S

Documents

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_9-1393303-7_S00F.3d_igs.zip

English

Customer View Model

ENG_CVM_9-1393303-7_S00F.3d_stp.zip

English

Customer View Model

ENG_CVM_9-1393303-7_S00F.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

MFINITY Modular Hard Wired Fuse and Relay Box

English

Automotive Relay Application Notes

English

General Purpose Power Relay, DC, Monostable, 1 Form A (NO), 50 A Contact Rating, 24 VDC Coil Voltage, 24 VDC Contact Voltage, Power Relay F



Product Specifications

Definitions General Purpose Relays

English