# 8PCV-06-006 ✓ ACTIVE

### Buchanan | BUCHANAN 8 Series

TE Internal #: 9-1437657-8

6 Position Barrier Strip, Tri-Barrier, Printed Circuit Pin Bottom Termination, Wire-to-Board, 11.1 mm [.438 in] Centerline, 1 Row,

**BUCHANAN 8 Series** 

View on TE.com >




Connectors > Terminal Blocks & Strips > Barrier Strips











Number of Positions: 6

Barrier Strip Style: Tri-Barrier

Bottom Termination Type: Printed Circuit Pin

Connector System: Wire-to-Board
Centerline (Pitch): 11.1 mm [.438 in]

## **Features**

### **Product Type Features**

Block Style	Flat Bottom with standoffs
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Levels	1
Number of Positions	6
Number of Rows	1
Electrical Characteristics	
Operating Voltage	600 V
Body Features	
Primary Product Color	Black
Product Orientation	Vertical
Barrier Strip Style	Tri-Barrier



#### **Contact Features**

Contact Base Material	Copper Alloy
PCB Contact Termination Area Plating Material	Tin
Contact Current Rating (Max)	30 A

### **Termination Features**

Bottom Termination Type Printed Circuit Pin	
---	--

### Mechanical Attachment

Top Termination Type	Wire Clamp Combo Head
Mounting Options	None
Screw Plating Material	Zinc
Screw Material	Steel
Thread Size	8-32
Screw Head Type	Wire Clamp Combo Head
Connector Mounting Type	Board Mount

## **Housing Features**

Housing Material	Thermoplastic
Centerline (Pitch)	11.1 mm[.438 in]

## Dimensions

Product Length	68.5 mm[2.697 in]
Wire Size	18 – 10 AWG, 22 – 10 AWG

## **Usage Conditions**

Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]

## Operation/Application

## **Industry Standards**

UL Flammability Rating	UL 94V-0
------------------------	----------

## **Packaging Features**

Packaging Method	Package
Packaging Quantity	100

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C


#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# Also in the Series BUCHANAN 8 Series





# Customers Also Bought






















### **Documents**

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_9-1437657-8\_R1.3d\_stp.zip

### English

**Customer View Model** 

ENG\_CVM\_CVM\_9-1437657-8\_R1.2d\_dxf.zip

### English

**Customer View Model** 

ENG\_CVM\_CVM\_9-1437657-8\_R1.3d\_igs.zip

English

#### 3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

## Datasheets & Catalog Pages

1-1773458-2\_BARRIER\_STRIPS\_QUICK\_REFERENCE\_GUIDE

English

6 Position Barrier Strip, Tri-Barrier, Printed Circuit Pin Bottom Termination, Wire-to-Board, 11.1 mm [.438 in] Centerline, 1 Row, BUCHANAN 8 Series



Agency Approvals

UL

English