




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **592 – 3260 CMA**

Mating Tab Width: **4.8 mm [.189 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
---------------------	--------

Electrical Characteristics

Voltage Rating	300 V
----------------	-------

Body Features

Insulation Material	Nylon
---------------------	-------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.8 mm[.189 in]
Mating Tab Thickness	.8 mm[.031 in]
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Tin
Crimp Type	Compression Crimp



Barrel Type	Closed
-------------	--------

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Product Length	20.88 mm[.822 in]
Compatible Insulation Diameter Range	3.56 mm[.14 in]
Wire Size	592 – 3260 CMA

Usage Conditions

Insulation Option	Partially Insulated
-------------------	---------------------

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece

Other

Barrel Color	Red
--------------	-----

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2392021-1 RED BATTERY DAHT KIT 110V (47689-4)	TE Part # 2323802-2 SSRMP-240D16 = Mini Puck,16A,240V AC	TE Part # 539691-2 ERGO DIE R.B.Y	TE Part # 169404 CERTI-LOK DIE
TE Part # 2323802-9 SSRMP-240D10R = Mini Puck,10A, 240V AC,R	TE Part # 2323802-7 SSRMP-240D25R = Mini Puck,25A, 240V AC,R	TE Part # 1-2323802-2 SSRMP-480D16R = Mini Puck,16A, 480V AC,R	TE Part # 169400 CERTI-LOK FRAME W/O DIES
TE Part # 2323802-6 SSRMP-480D10 = Mini Puck,10A,480V AC	TE Part # 2323802-4 SSRMP-480D25 = Mini Puck,25A,480V AC	TE Part # 2323802-1 SSRMP-240D25 = Mini Puck,25A,240V AC	TE Part # 2392021-2 RED BATTERY DAHT KIT 220V (47689-4)
TE Part # 47386-4 DAHT PG PIDG 26-16 ASSY	TE Part # 58423-1 DIE, RBY IS9252	TE Part # 58433-3 PRO CR ASSY, RBY IS9252	TE Part # 1-2323802-1 SSRMP-480D25R = Mini Puck,25A, 480V AC,R



TE Part # 1-2323802-3
SSRMP-480D10R = Mini Puck,10A, 480V AC,R

TE Part # 525690
DAHT PG PIDG 20-18 ASSY

TE Part # 2323802-3
SSRMP-240D10 = Mini Puck,10A,240V AC

TE Part # 2323802-8
SSRMP-240D16R = Mini Puck,16A, 240V AC,R

Customers Also Bought

TE Part #130532
PIDG SPADE

TE Part #316400-1
2.5 SIGNAL D/L REC CONT. L L/P

TE Part #926901-3
UNIV-MNL BUCHSE

TE Part #322872
SOLIS R HT 22-16COMM22-18MIL 6

TE Part #CAT-T3437-T548
TMS-SCE Military Grade Sleeves

TE Part #2213775-3
AV16 SPM 0.4VA POWER LED RED 12V

TE Part #170605-000
382A023-100/180-0

TE Part #2-1105050-2
HN.D-C-ST1.AU.0,5

Documents

Product Drawings

187 PIDG FASTON REC

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_9-160483-5_J.2d_dxf.zip

English

Customer View Model

ENG_CVM_9-160483-5_J.3d_igs.zip

English

Customer View Model

ENG_CVM_9-160483-5_J.3d_stp.zip

English

3D PDF



3D

Customer View Model

[ENG_CVM_CVM_9-160483-5_L.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_9-160483-5_L.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_9-160483-5_L.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.