CII

TE Internal #: 9-1617805-8

Time Delay Relay, DC, 2 Form C DPDT-CO, 10 A Contact Rating,

Chassis Mount, Hermetically Sealed, 125 °C [257 °F]

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: Time Delay Relay

Current Type: DC

Contact Arrangement: 2 Form C DPDT-CO

Contact Current Rating: 10 A

Main Termination & Connection Type: Solder Hook Terminals

Features

Product Type Features

Froduct Type realures	
Relay & Contactor Type	Time Delay Relay
Configuration Features	
Contact Arrangement	2 Form C DPDT-CO
Electrical Characteristics	
Input Voltage	28 VDC
Contact Current Rating	10 A
Body Features	
Enclosure Type	Hermetically Sealed
Contact Features	
Contact Material	Silver Cadmium Oxide
Termination Features	
Main Termination & Connection Type	Solder Hook Terminals
Coil Termination & Connection Type	Solder Hook Terminals
Mechanical Attachment	
Product Mounting Feature Type	Mounting Brackets

Chassis Mount

Product Mount Type

Dimensions



Product Width	25.79 mm[1.01 in]
Product Length	43.6 mm[1.72 in]
Product Height	25.4 mm[1 in]
Usage Conditions	
Operating Temperature Range	-55 – 125 °C
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Type of Control	Fixed
Indicator Type	No Indicator
Delay Time	5 seconds
Mode of Operation	Delay on Operate
Repeatability (Max)	±10%

DC

Product Compliance

Current Type

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
	·
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides




on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Customers Also Bought






















Documents

Product Drawings
TD228-5001S=TDFO 5 SEC M83726/28-5001S

English

Time Delay Relay, DC, 2 Form C DPDT-CO, 10 A Contact Rating, Chassis Mount, Hermetically Sealed, 125 °C [257 °F]



Datasheets & Catalog Pages
High_Performance_Relays_Section5

English