


AMP POWER TAP

TE Internal #: 9-55556-0 Power Tap, Terminates To Printed Circuit Board, 10 Position, 2.54 mm [.1 in] Centerline, Vertical, Stamped & Formed, Tin (Sn), Power Terminals

View on TE.com >

Terminals & Splices > Power Terminals



Power Terminal Type: Power Tap Product Terminates To: Printed Circuit Board Number of Positions: 10 Contact Current Rating (Max): 25 A Centerline (Pitch): 2.54 mm [.1 in]

Features



Product Type Features

Footprint	7.62 x 2.54 mm[.3 x .1 in]
Power Terminal Type	Power Tap
Configuration Features	
Number of Positions	10
PCB Mount Orientation	Vertical
Body Features	
Terminal Profile	Low
Contact Features	
Contact Current Rating (Max)	25 A
Contact Fabrication	Stamped & Formed
Contact Mating Area Plating Material	Tin (Sn)
Contact Mating Area Plating Material Thickness	3.81 μm[150 μin]
PCB Contact Termination Area Plating Material	Tin
PCB Contact Termination Area Plating Material Thickness	3.81 μm[150 μin]

9-55556-0

Power Tap, Terminates To Printed Circuit Board, 10 Position, 2.54 mm [.1 in] Centerline, Vertical, Stamped & Formed, Tin (Sn), Power Terminals



Contact Base Material	Copper Alloy
Termination Features	
Termination Method to PCB	Through Hole - Press-Fit
Termination Method to Wire & Cable	Tap Screw
Product Terminates To	Printed Circuit Board
Mechanical Attachment	
Thread Size	6-32
Housing Features	
Housing Material	Nylon GF
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
PCB Thickness (Recommended)	1.57 – 3.18 mm[.062 – .125 in]
Product Length	12.7 mm[.5 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]

Packaging Features

Pack	aging	g Meth	bc
	5 5	/	

Bulk

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

9-55556-0

Power Tap, Terminates To Printed Circuit Board, 10 Position, 2.54 mm [.1 in] Centerline, Vertical, Stamped & Formed, Tin (Sn), Power Terminals



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought



TE Part #5-1622796-9 YR1 0.1% 14K7 TE Part #2-208224-1 CPC RECPT ASSEMBLY SIZE 23-37 TE Part #8-2176633-1 SQMB10 2K2 (WIRE) 5% TE Part #5499923-1 A/L UNIV HDR 10P VERT LAT



Documents

Product Drawings 10 POWER TAP ASSY WITH SCREW #6-32

English

CAD Files

Customer View Model ENG_CVM_CVM_9-55556-0_T.2d_dxf.zip

English

9-55556-0

Power Tap, Terminates To Printed Circuit Board, 10 Position, 2.54 mm [.1 in] Centerline, Vertical, Stamped & Formed, Tin (Sn), Power Terminals



3D PDF

3D

Customer View Model ENG_CVM_CVM_9-55556-0_T.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_9-55556-0_T.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English