




Positive Lock | Positive Lock 250

TE Internal #: 927855-6

Quick Disconnect Receptacle, 17 – 13 AWG, 1.03 – 2.62 mm² Wire,
6.35 mm [.25 in] Tab Width, Straight, Phosphor Bronze, Positive
Lock 250

[View on TE.com >](#)

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **1.03 – 2.62 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	22.3 mm[.88 in]
Compatible Insulation Diameter Range	2.11 – 3.1 mm[.083 – .122 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	1.03 – 2.62 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Packaging Features

Packaging Quantity	500
Packaging Method	Loose Piece/Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2063527-2
SDE FASTON 110 0.5-2.5mm2 DIE SET

TE Part # 539734-2
DIE SPT 4MM

TE Part # 2063527-1
SDE FASTON 110 0.5-2.5mm2 ASSY

TE Part # 169400
CERTI-LOK FRAME W/O DIES

Also in the Series | Positive Lock 250

Automotive Terminals(1)


Crimp Terminal Housings(177)

Insertion & Extraction Tools(3)


Insulation Boots & Sleeves(5)

Quick Disconnects(173)

Customers Also Bought




TE Part #180409-2
FF 250 TAB 4-6MM2 PTBR LP



TE Part #280099
FF 250 TAB HSG 8P NYLON CLEAR



TE Part #4-1746741-4
RITS CONN. SOCKET ASSY 4P GREEN



TE Part #3-917809-3
DYNAMIC D-5 TAB HSG D/R 6P X-Y




TE Part #464244-E
SRCA 1,27 6 F 1 IDC22 137 E1 094 1,27 TR



TE Part #1623925-8
CFR100 5% 150R




TE Part #154719
250 HSG. PL MKI REC. BLACK



TE Part #160773-3
PL LP RECEPTACLE 0.5-1.5 MM2 TPBR



TE Part #61-0040-011-P00
CONTACT PIN 3,6 MM



TE Part #839087-E
IDCCS SRC 1,27 8 * SFX NXX 100 PVC

Documents

Product Drawings

PL RECEPTACLE 1.0-2.5 MM2 PTP CUSN 30

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_927855-6_E_c-927855-6-e.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_927855-6_E_c-927855-6-e.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_927855-6_E_c-927855-6-e.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

927855-6

Quick Disconnect Receptacle, 17 – 13 AWG, 1.03 – 2.62 mm² Wire, 6.35 mm [.25 in]
Tab Width, Straight, Phosphor Bronze, Positive Lock 250



1654742_HOUSEHOLD_APPLIANCES_RAST5

English