




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **1021 – 2048 CMA**

Mating Tab Width: **2.8 mm [.11 in]**

Features

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.79 mm[.031 in]
Terminal Orientation	Straight
Contact Base Material	Copper Tin Alloy
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Locking Lance Height	1.2 mm[.047 in]
----------------------	-----------------



Mating Retention Type

Locking Lance

Dimensions

Product Length	22.5 mm[.886 in]
Compatible Insulation Diameter Range	1.4 – 2.3 mm[.055 – .09 in]
Wire Size	1021 – 2048 CMA

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 130 °C[-40 – 266 °F]

Packaging Features

Packaging Quantity	4000
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

TE Part # 1-1579007-4
EXTRACTION TOOL

TE Part # 4-1579007-3
EXTRACTION TOOL KIT

TE Part # 7-2151379-7
OCEAN_2.0_SPARE_PART_KIT-080F110OV

TE Part # 2305570-1
Strip Terminal Cutter-Side Feed-No Crimp

TE Part # 2151379-1
OCEAN_2.0_Applicator-S-080F110OV-RSM

TE Part # CAT-T4827-CH8172
Timer Connector Housing

TE Part # 2151379-2
OCEAN_2.0_Applicator-S-080F110OV-RSA

Also in the Series | FASTIN-FASTON 110

Automotive Housings(6)

Automotive Terminals(5)

Crimp Terminal Housings(34)

Insertion & Extraction Tools(3)

Quick Disconnects(78)

Customers Also Bought




TE Part #928781-2
FF 110 TAB 1.0-2.5 MM2 PTP CUZN30



TE Part #CAT-T4827-CH8172
Timer Connector Housing




TE Part #6-1625890-9
2W SM M/OX 5% 820R



TE Part #963900-1
TAB A 1.6x0.6 CONTACT CS SRC Sn



TE Part #927783-3
JPT REC 2.8 Contact SRC Sn (LP)



TE Part #828801-2
2X 3P MESSERLEI 3,0

Documents

Product Drawings

FF 110 TAB 0.5-1 MM2 .080 F PTP CUZN30

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_928930-5_P.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_928930-5_P.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_928930-5_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

2,8 mm Flachstecker

English

Application Specification

English

Application Specification

German

Application Specification

English

928930-5

Quick Disconnect Tab, 20 – 17 AWG, .5 – 1 mm² Wire, 1021 – 2048 CMA, 2.8 mm [.11 in] Tab Width, Straight, Copper Tin Alloy, FASTIN-FASTON 110

