




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **1.03 – 2.62 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

|                 |        |
|-----------------|--------|
| Insertion Force | Normal |
|-----------------|--------|

Configuration Features

|                                   |               |
|-----------------------------------|---------------|
| Compatible With Wire & Cable Type | Discrete Wire |
| Connection Capacity               | Single        |

Contact Features

|                                |                 |
|--------------------------------|-----------------|
| Quick Disconnect Terminal Type | Tab             |
| Mating Tab Width               | 6.35 mm[.25 in] |
| Mating Tab Thickness           | .81 mm[.032 in] |
| Terminal Orientation           | Straight        |
| Contact Base Material          | Brass           |
| Terminal Plating Material      | Tin             |
| Crimp Type                     | F-Crimp         |
| Barrel Type                    | Open            |

Termination Features

|  |  |
|--|--|
|  |  |
|--|--|



|                       |              |
|-----------------------|--------------|
| Product Terminates To | Wire & Cable |
|-----------------------|--------------|

Mechanical Attachment

|                         |                |
|-------------------------|----------------|
| Locking Lance Height    | 1.4 mm[.06 in] |
| Wire Insulation Support | With           |
| Mating Retention Type   | Locking Lance  |

Dimensions

|                                      |                              |
|--------------------------------------|------------------------------|
| Product Length                       | 27.9 mm[1.098 in]            |
| Compatible Insulation Diameter Range | 2.1 – 2.9 mm[.083 – .114 in] |
| Terminal Material Thickness          | .41 mm[.016 in]              |
| Wire Size                            | 1.03 – 2.62 mm²              |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Insulation Option           | Uninsulated                |
| Operating Temperature Range | -40 – 110 °C[-40 – 230 °F] |

Packaging Features

|                    |            |
|--------------------|------------|
| Packaging Quantity | 3000       |
| Packaging Method   | Strip/Reel |

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

|                                               |                                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                     |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                     |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                       |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2025 (247)<br>Candidate List Declared Against: JAN 2025 (247)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                           |
| Solder Process Capability                     | Not applicable for solder process capability                                                                                  |


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



**KIT**

TE Part # 7-2150195-7  
OCEAN\_2.0\_SPARE\_PART\_KIT-110F140OV



TE Part # 880638-2  
.110 SERIES FASTIN-



TE Part # 2150195-2  
OCEAN\_2.0\_Applicator-E-110F140OV-REA



TE Part # 1-1579007-4  
EXTRACTION TOOL



TE Part # 880636-2  
FF 250 TAB 1.0-2.5 MM2 0.39 X 13.2 TPBR



TE Part # 4-1579007-3  
EXTRACTION TOOL KIT

Also in the Series | FASTIN-FASTON 250



Crimp Terminal Housings(195)



Insertion & Extraction Tools(2)



Quick Disconnects(216)


Customers Also Bought




TE Part #62048-2  
250 FASTON REC 18-14 AWG TPBR



TE Part #928343-6  
STD-TIM GEH 6P




TE Part #3-643814-4  
04P MTA100 CONN ASSY POL RIB



TE Part #1-172233-9  
2P MINI UNIV FREE HANG BLACK



TE Part #293041-2  
FF 250 TAB 0.35-1.0MM2 TPBR




TE Part #321235  
RECEPT, FASTON SPLICE 22-10



TE Part #2350891-1  
20POS,HYBRID,PIN HSG ASSY,SLD, COD A



TE Part #2238019-1  
VAL-U-LOK SKT BR SN 22-26AWG



TE Part #2238016-1  
VAL-U-LOK PIN BR SN 18-22AWG



TE Part #925575-1  
STC REC 6.3 Contact SRC Sn

Documents

Product Drawings

FF 250 TAB 1.0-2.5MM2 TBR

English

CAD Files

Customer View Model

ENG\_CVM\_CVM\_928962-2\_G.2d\_dxf.zip

English

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_928962-2\_G.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_928962-2\_G.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



1654742\_HOUSEHOLD\_APPLIANCES\_RAST5

English

Product Specifications

Application Specification

English