

AMP | Junior Timer


TE Internal #: 963121-1

8 Position Housing, Housing for Female Terminals, Wire-to-Wire, 6 mm [.236 in] Centerline, Brown, Wire & Cable, Power, Junior Timer

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Timer Connector Housing



Number of Positions: 8

Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 2.8 mm [.11 in]

Connector System: Wire-to-Wire

Centerline (Pitch): 6 mm [.236 in]

All Timer Connector Housing (437)

Features

Product Type Features

Product Type Features	
Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	No
Primary Locking Feature	On the Terminal
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	8
Number of Rows	2
Electrical Characteristics	
Nominal Voltage Architecture	12 V
Body Features	
Primary Product Color	Brown
Contact Features	
Contact Size	2.8mm

Receptacle

Contact Type



Mating Tab Width	2.8 mm[.11 in]
Contact Current Rating (Max)	30 A
Mechanical Attachment	
Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA
Centerline (Pitch)	6 mm[.236 in]
Dimensions	
Product Width	12.6 mm[.496 in]
Row-to-Row Spacing	5 mm[.197 in]
Product Length	34.5 mm[1.358 in]
Connector Height	23 mm[.906 in]
Usage Conditions	
Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
UL Flammability Rating	UL 94V-2
Packaging Features	
Packaging Method	Box
Other	
Serviceable	No
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Also in the Series | Junior Timer









Customers Also Bought



TE Part #CAT-T4827-CH8172
Timer Connector Housing

















Documents

Product Drawings

JUNIOR TIMMER HOUSING 8POS, AS

English

CAD Files

Customer View Model

ENG_CVM_963121-1_A2.3d_igs.zip

English

Customer View Model

ENG_CVM_963121-1_A2.3d_stp.zip

English

Customer View Model

ENG_CVM_963121-1_A2.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

8 Position Housing, Housing for Female Terminals, Wire-to-Wire, 6 mm [.236 in] Centerline, Brown, Wire & Cable, Power, Junior Timer



Datasheets & Catalog Pages 889759_3_Timer_Interconnection_System

English